Weidmüller ⢱

BS 25 O.IH SAKT1

Product image

Fixing screws fix the short current bridge within the application. If the short current bridge is slided between two adjacent terminal blocks into the short circuit position, it can be fixed by means of a fastening screw. This ensures a permanent connection or short circuit.

General ordering data

Version	Mounting screw (Terminal), 3.00 mm, Brass, Depth: 28.7 mm, Width: 5.5 mm, Height: 5.5 mm
Order No.	0334700000
Type	BS 25 O.IH SAKT1
GTIN (EAN)	4008190118839
Qty.	50 pc(s).

Creation date November 26, 2024 12:41:01 PM CET

BS 25 O.IH SAKT1

Technical data

Dimensions and weights

Depth	28.7 mm	Depth (inches)	1.13 inch
Height	5.5 mm	Height (inches)	0.217 inch
Width	5.5 mm	Width (inches)	0.217 inch
Diameter	5.5 mm	Net weight	1.7 g

Temperatures

Storage temperature	-25 °C...55 °C

Material data

Material	Brass	Colour	beige

System specifications

Version	for cross-connection link

Additional technical data

Installation advice	Direct mounting	Type of mounting	when screwed in

Dimensions

Diameter	5.5 mm	Metric size of the thread, external	3 mm

General

Installation advice	Direct mounting

Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ETIM 8.0	EC002848	ETIM 9.0	EC002848
ECLASS 9.0	27-14-11-92	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-14-11-92	ECLASS 11.0	27-14-11-92
ECLASS 12.0	27-14-11-92	ECLASS 13.0	27-25-03-90
ECLASS 14.0	27-25-03-90		

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c
REACH SVHC	Lead 7439-92-1
SCIP	cabfa93a-285a-4cc9-a7cb-2fefa00bc7a4

Approvals

ROHS	Conform

Downloads

User Documentation	StorageConditionsTerminalBlocks
Catalogues	[Catalogues in PDF-format](Catalogues-in-PDF-format)
Brochures	

Creation date November 26, 2024 12:41:01 PM CET