

# Product data sheet

## Characteristics

# QGL22080

Circuit breaker, PowerPacT Q, 80A, 2 pole, 240VAC, 65kA, lugs, thermal magnetic, 80%



### Main

|                           |                 |
|---------------------------|-----------------|
| Range                     | PowerPact       |
| Product name              | PowerPact Q     |
| Product or Component Type | Circuit breaker |
| Device Application        | Distribution    |

### Complementary

|  |  |
|--|--|
| Line Rated Current                     | 80 A   |
| Number of Poles                        | 2P   |
| Control type                           | Operating handle   |
| Breaking capacity code                 | G  |
| Breaking capacity                      | 65 KA 120/208 V AC 50/60 Hz UL<br>65 kA 240 V AC 50/60 Hz UL                                       |
| [Ue] rated operational voltage         | 240 V AC 50/60 Hz UL   |
| Network Frequency                      | 50/60 Hz   |
| [Uimp] rated impulse withstand voltage | 8 kV UL  |
| Trip unit technology                   | Thermal-magnetic   |
| Magnetic tripping current              | 1800 A   |
| Magnetic hold current                  | 1000 A   |
| Continuous current rating              | 80 %   |
| Utilisation category                   | Category A   |
| Mechanical durability                  | 1000 Cycles loaded<br>5000 cycles no load  |
| Local signalling                       | 1 trip indicator green)  |
| Mounting mode                          | Unit mount lug)  |
| Mounting Support                       | Lug  |
| Electrical connection                  | Lugs, load<br>Lugs, line   |
| Tightening torque                      | 247.82 lbf.in (28 N.m) 0.04...0.23 in <sup>2</sup> (25...150 mm <sup>2</sup> ) (AWG 4...300 kcmil) |
| Power wire stripping length            | 0.87 in (22 mm)  |
| Height                                 | 6.47 in (164.34 mm)  |
| Width                                  | 3 in (76.20 mm)  |
| Depth                                  | 3.93 in (99.82 mm)   |
| Circuit breaker application            | HACR rated   |

### Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | UL<br>CSA<br>NEMA<br>NOM-003-SCFI-2000 |
| Product certifications                | UL[RETURN]CSA[RETURN]NOM               |
| Ambient Air Temperature for Operation | 104...158 °F (40...70 °C)              |

## Ordering and shipping details

|                   |                                 |
|-------------------|---------------------------------|
| Category          | 00005-QO,Q2L 2P ENCL & BREAKERS |
| Discount Schedule | DE2A                            |
| GTIN              | 785901461951                    |
| Returnability     | Yes                             |
| Country of origin | MX                              |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 5.56 in (14.127 cm)    |
| Package 1 Width              | 5.81 in (14.757 cm)    |
| Package 1 Length             | 9.75 in (24.765 cm)    |
| Package 1 Weight             | 3.34 lb(US) (1.515 kg) |

## Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product  |
| California proposition 65   | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH free of SVHC          | Yes  |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a>  |
| Mercury free                | Yes  |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>   |
| RoHS exemption information  | <a href="#">Yes</a>  |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>  |
| PVC free                    | Yes  |
| Halogen content performance | Halogen free product   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|