# Product data sheet Characteristics

## **NSYSFEB**

Lifting eyebolts, PanelSeT SFN, Spacial SF, steel, M12, set of 4



#### Overview

Lead time Usually Ships within 4 Weeks



#### Main

Spacial	
Lifting accessory	
Lifting eye	
Multi-purpose	
Enclosure top	
Directly in the axis of the uprights	
Spacial Spacial SF Spacial Spacial SFHD Prisma Prisma PH Spacial Spacial SFM	
4 eyebolt	
Set of 1	
	Lifting accessory  Lifting eye  Multi-purpose  Enclosure top  Directly in the axis of the uprights  Spacial Spacial SF Spacial Spacial SFHD Prisma Prisma PH Spacial Spacial SFM  4 eyebolt

#### Complementary

Material	Cast steel	
Surface Finish	Galvanized	
Fixing mode	Screwed	
Permanent permissible load	749.57 lb(US) (340 kg) for 1 eyebolt vertical direction	
Height	2.46 in (62.5 mm)	
Width	2.17 in (55 mm)	
Depth	0.94 in (24 mm)	
Diameter	1.14 in (29 mm)	
ISO thread	M12	

#### Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606485131542
Returnability	Yes
Country of origin	ES

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.36 in (6.000 cm)
Package 1 Width	3.94 in (10.000 cm)
Package 1 Length	4.13 in (10.500 cm)
Package 1 Weight	27.20 oz (771.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	41.72 lb(US) (18.924 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	192
Package 3 Height	17.72 in (45.000 cm)
Package 3 Width	31.50 in (80.000 cm)
Package 3 Length	47.24 in (120.000 cm)
Package 3 Weight	360.22 lb(US) (163.392 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

#### Contractual warranty

Contraction Warranty		
Warranty	18 months	