RXZE14P

push in socket with clamp, Harmony Electromechanical Relays, for RXM relays, 12A 2CO, 6A 4CO, push in terminals, separate contact





Main

Range of Product	Harmony Electromechanical Relays Harmony Timer Relays
Product or Component Type	Socket
Contact terminal arrangement	Separate
Product compatibility	Plug-in relay RXM 2 C/O Plug-in relay RXM 4 C/O
Shape of pin	Flat
Device short name	RXZ
Sale per indivisible quantity	10

Complementary

[Ith] conventional free air thermal current	12 A 2 C/O relays 6 A 4 C/O relays
[Ue] rated operational voltage	250 V IEC 300 V UL
Connections - terminals	Spring clamp terminals (push 'n stay), 1 x 0.51 x 1.5 mm² AWG 20AWG 16) flexible with cable end Spring clamp terminals (push 'n stay), 1 x 0.51 x 1.5 mm² AWG 20AWG 16) solid without cable end
Fixing mode	Clip-on 35 mm symmetrical DIN rail)
Marking	CE
Height	3.35 in (85 mm)
Length	3.86 in (98 mm)
Width	1.22 in (31 mm)
Net Weight	0.18 lb(US) (0.080 kg)

Environment

[Uimp] rated impulse withstand voltage	4 kV	
[Ui] Rated Insulation Voltage	250 V	
Overvoltage category	III	
Pollution degree	3	-
Standards	IEC 61984	
Product Certifications	CSA[RETURN]Lloyd's[RETURN]UL[RETURN]EAC	
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)	
Ambient Air Temperature for Operation	-40131 °F (-4055 °C)	
IP degree of protection	IP20	
Dielectric strength	2500 V	

Ordering and shipping details

Category	21128-ZELIO ICE CUBE RELAY ACCESSORIES
Discount Schedule	CP2
GTIN	3606481465764
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.22 in (3.1 cm)
Package 1 Width	3.35 in (8.5 cm)
Package 1 Length	3.98 in (10.1 cm)
Package 1 Weight	2.61 oz (74 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.54 in (9 cm)
Package 2 Width	6.30 in (16 cm)
Package 2 Length	8.03 in (20.4 cm)
Package 2 Weight	31.60 oz (896 g)
Unit Type of Package 3	S03
Number of Units in Package 3	70
Package 3 Height	11.81 in (30 cm)
Package 3 Width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)
Package 3 Weight	14.80 lb(US) (6.713 kg)


Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.


Contractual warranty

ontractal varianty	
Warranty	18 months

Dimensions



Wiring




Installation




Installation

Push In (Insert Cable)



Uninstallation

Pull Out (Remove Cable)



(1): Press

(2): Pull Wire