

LADR23

Time delay auxiliary contact block, TeSys
Deca, 1NO + 1NC, off delay 1-30s, front, spring
terminals



Main

Range	TeSys TeSys Deca
Product name	TeSys Deca
Product or Component Type	Time delay auxiliary contact block
Range compatibility	TeSys D CAD[RETURN]TeSys D LC1D[RETURN]TeSys Deca CAD[RETURN]TeSys Deca LC1D
Mounting Location	Front
Pole contact composition	1 NO + 1 NC
Contacts operation	Time delay
Timer type	Off delay
Time delay range	1...30 s
[Ue] rated operational voltage	690 V AC 25...400 Hz
[Ie] rated operational current	6 A at 120 V AC-15 1.04 A at 690 V AC-15 0.55 A at 125 V DC-13 0.1 A at 600 V DC-13
[Ui] rated insulation voltage	690 V IEC 60947-5-1 600 V UL 600 V CSA
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C))
Standards	GB/T 14048.5 EN/IEC 60947-5-1
Product Certifications	CB[RETURN]UL[RETURN]CSA[RETURN]CCC[RETURN]TUV[RETURN]VDE[RETURN]CE[RETURN]UL[RETURN]CSA[RETURN]CCC[RETURN]TUV[RETURN]VDE[RETURN]CE

Complementary

Irms rated making capacity	140 A AC 250 A DC
Permissible short-time rating	100 A 140 °F (60 °C) 1 s 120 A 140 °F (60 °C) 500 ms 140 A 140 °F (60 °C) 100 ms
Protection type	GG fuse 10 A
Mechanical durability	5 Mcycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Non-overlap time	1.5 Ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact
Insulation resistance	> 10 MOhm
Connections - terminals	Spring terminals 2 0.00 in ² (2.5 mm ²)flexible without cable end Spring terminals 2 0.00 in ² (2.5 mm ²)rigid
Height	1.89 in (48 mm)
Width	1.73 in (44 mm)
Depth	2.40 in (61 mm)
Color	Dark grey

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Environmental characteristic	Normal environment
IP degree of protection	IP2X conforming to IEC 60529
Protective treatment	TH IEC 60068
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C)
Operating altitude	9842.52 ft (3000 m)

Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	3389110821765
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.05 in (5.2 cm)
Package 1 Width	2.56 in (6.5 cm)
Package 1 Length	1.89 in (4.8 cm)
Package 1 Weight	2.72 oz (77.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	2.05 in (5.2 cm)
Package 2 Width	5.51 in (14.0 cm)
Package 2 Length	9.45 in (24.0 cm)
Package 2 Weight	27.72 oz (786.0 g)
Unit Type of Package 3	S02
Number of Units in Package 3	70
Package 3 Height	5.91 in (15.0 cm)
Package 3 Width	11.81 in (30.0 cm)
Package 3 Length	15.75 in (40.0 cm)
Package 3 Weight	12.85 lb(US) (5.83 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------