



[Click For Larger Image](#)

Lumatrol T, ET and ST Series Wire-in Photocontrols

LUMITROL ET ST SERIES:

Features	Description	ALR	Tork	Voltage	Rating
----------	-------------	-----	------	---------	--------

Add to Cart

Swivel T-Series (ST) is equipped with a swivel mount which allows installer to swivel light sensitive element to the best position for operation.

Features	Description
Housing:	Weatherproof Lexan housing or vandal proof die cast aluminum housing. (Model T15AL only)
Photocell:	Broad surface sensing element
Turn-on:	1 to 3 foot-candles. External light level slide allows field adjustment between 3 to 10 foot-candles
Turn-on/ off Ratio:	1:3
Switch Type:	Single-pole, single-throw. Contact position at night normally closed
Temperature Range:	-40 Degree to 158 Degree F
Lead Wire:	Moisture proof, color coded lead wire. Wire length: 6 inches
Threaded Stem:	1/2 inch-14 thread, and fits 1/2 inch knock out. Swivel T-Series (ST) is equipped with a swivel mount which allows installer to swivel light sensitive element to the best position for operation
Dimensions T Series:	2" high, 1-1/2" wide, 1" deep
Dimensions ST Series:	2" high, 1-1/2" wide, 1" deep (body); 2" high, (stem)
Dimensions ET Series:	3-1/2" long, 1-1/4" wide, 1-1/4" high

Lumatrol T, ST, and ET Series Replacement Comparison Chart

Model	Intermatic	ALR	Tork	Voltage	Rating
-------	------------	-----	------	---------	--------

Model	Intermatic	ALR	Tork	Voltage	Rating	
ST15*	K1121 / K1221	SAT-15 / SPT168	3020 / 2001	120	1100 VA	
T15*	K4121	AT15 / PT-15	2101	120	1100 VA	
ST168*	K4224 / K4222 / K4233	SAT-168 / SPT168	-	208-277	1100 VA	
T168*	K4124 / K4122 / K4133	AT168 / PT168	2104	208-277	1100 VA	
ST19**	K4235	SAT-19 / SPT168	-	480	1800 VA	
T19**	K4135	AT19 / PT19	-	480	1800 VA	
ST347**	-	-	-	347	1800 VA	
ET15*	-	TL115	2001	120	1100 VA	
ET168*	-	TL168	2002	208-277	1100 VA	

** Dimensions: 3" high, 2" wide, 1 3/8" deep

* cULus Certified

Additional Information

Weight	1 lb.
Dimensions	7 x 7 x 4 in.
Lumitrol ET ST Series	ET168, ET15, ST15, ST168, T168, ST19, T19, ST347, T15