



Brady PermaSleeve Wire Marking Sleeves

Part Number: 3PS-125-2-WT

Product Number: 32507

Material Description: PermaSleeve® Heat-Shrink Polyolefin

QTY/UOM: 2,500/Package

Specifications for Brady PermaSleeve Wire Marking Sleeves

Part Number	3PS-125-2-WT
Recommended Ribbon Series	The Brady R6600 Series and R4300 Series black ribbons are recommended for best thermal transfer print performance. The Brady R4502S silver ribbon and the R6700 Series white ribbons are recommended for thermal transfer printing of black markers. The Brady R5000 Series high performance ribbon is recommended for best dot matrix print performance.
Adhesive	None
Agency Approval(s)/Compliance	SAE-DTL-23053/5 Class 1, SAE-AS-81531, MIL-STD-202, UL Recognized
Application	Wire & Cable Marking, Panel Identification
Brady Material Number	B-342
Color	White
Description	Brady PermaSleeve Wire Marking Sleeves
Finish	Matte
Height (in)	0.235"
Height (mm)	6.000 mm
Label Type/Style	Sleeve
Material Description	PermaSleeve® Heat-Shrink Polyolefin
Material Type	Polyolefin
Panel Application	Wire & Cable Marking
Printable Sides	Two-Sided Printable
Printer Compatibility	Brady 1244, Brady 1344, Brady 2461, Brady 3481, Brady 6441, Brady 300X-Plus II, Brady 360X-Plus II, Brady 600X-Plus II, Tagus T200, Tagus T300, Thermal Transfer Printers, Sleeve & Datab Series, IP300, IP600, BBP72, BradyPrinter PR Plus
Product Number	32507
QTY/UOM	2,500/Package
Range of Wire Diameter (in)	0.046" - 0.110"
Range of Wire Diameter	1.17 mm - 2.79 mm

(mm)	
Shrink Ratio	3-to-1
UPC Code	66282032507
Vertical Repeat	0.500" (12.70 mm)
Width (in)	2.000"
Width (mm)	50.800 mm
Wire Gauge	22 to 16
RoHS Compatibility	Pass 2011/65/EU