



Overview

Lead time	Usually in Stock
-----------	------------------



General

Provided Equipment	Mounting Hardware Rack Mounting brackets Serial configuration cable
--------------------	---

Physical

Cable length	8 ft (2.44 m)
Color	Black
Depth	9.29 in (23.6 cm)
Height	1.73 in (4.4 cm)
Product Weight	9.70 lb(US) (4.4 kg)
Width	17.01 in (43.2 cm)

Input

Input Frequency	50/60 Hz
Line Rated Current	16 A
Plug standard	NEMA L5-20P
Max line current	20 A
Input current limits	20 A
Load Capacity	1920 VA
Nominal Input Voltage	120 V

Output

Max current draw	20 A
Number of power socket outlets	10 NEMA 5-20R
Protection Type	Without circuit breaker
Output voltage	120 V

Conformance

Standards	EN 55022 Class A FCC Part 15 class A
-----------	---

Environmental

Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)




Ordering and shipping details

GTIN	00731304333500
Package weight(Lbs)	13.60 lb(US) (6.17 kg)

Packing Units

Package 1 Height	4.49 in (11.4 cm)
Package 1 width	23.62 in (60 cm)
Package 1 Length	14.02 in (35.6 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------