

RAZOR

OVERVIEW

The Razor series' ultra-slim design is perfect for any small space and allows for flexible installation, particularly in confined areas or when facing constraints such as beams, ceiling joists or air ducts.

FEATURES

■ 3 COLOR TEMPERATURES AND SELECTABLE CCT

27 K, 3 K and 4 K, available in select styles (white finish only)
3-CCT: 3 K, 4 K and 5 K, available in all styles

■ 4 FINISHES

White, black, satin chrome and bronze

■ RATINGS AND CERTIFICATIONS

IC rated
Wet location rated
Airtight rated ASTM E283-04
ETL certified for USA and Canada
Fire rated FT4/FT6 wires (UL 2464)

- Largest assortment of shapes, sizes, finishes and color temperatures
- Widest range of compatible LED dimming options
- Designed for both forward phase and reverse phase dimmers at 120V
- Available with 0-10v dimming at 120-277V

■ WARRANTY AND LED LIFE

5 year warranty and a 50,000-hour LED life

■ EASY INSTALLATION

Each unit includes a junction box with driver, pressure-fit spring clips and Quick Connect wire connectors for fast and easy installation.

Heavy duty mounting clips are designed for sturdy installation and prevent springs from falling off during installation.

Large flange feature allows for compensation if hole cut-outs are done incorrectly.



RAZOR

ULTRA THIN RECESSED DOWNLIGHT **LED**

The Razor flat design with low profile allows the light unit to slip under a joist. Whether a home or commercial application, its superior brightness and low power usage offer an ideal lighting solution.

FINISH



WHITE



BLACK



BRONZE



SATIN CHROME

SIZE & MODELS



3"
420 lumens
RZR-CCT-300

4"
680 lumens
RZR-CCT-400

5"
780 lumens
RZR-CCT-500

6"
1000 lumens
RZR-CCT-600

8"
1450 lumens
RZR-CCT-800

COLOR TEMPERATURE

27 K, 3 K & 4 K
3-CCT: 3 K, 4 K & 5 K

* Available in a 120-277V option (0-10v dim)

** Single color temperature options available in select sizes, in white finish only

