



ZCK E64

## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ1 ZCKJ8H29 ZCKJ1H29 ZCKJ5 ZCKJ5H29 ZCKJ7H29 ZCKJD39H29 ZCKJ2H7 ZCKJD35H7 ZCKJ9H7 ZCKJ21H29 ZCKJD31 ZCKJ6H7 ZCKJ9 ZCKJD39 ZCKJ11H29 ZCKJ5H7 ZCKJD37 ZCKJD37H29 ZCKJ21H7 ZCKJD31H29 ZCKJ2H29 ZCKJD37H7 ZCKJ21 ZCKJ7H7 ZCKJ11 ZCKJ11H7 ZCKJD35 ZCKJ7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ9H29  
ZCKJD39H7  
ZCKJD35H29  
ZCKJ2  
ZCKJ1H7  
ZCKJ8  
ZCKJ6H29  
ZCKJD31H7  
ZCKJ6  
ZCKJ8H7

Movement of operating head	Linear
Type of operator	Side roller plunger spring return metal (with horizontal roller)
Type of approach	Lateral approach, 2 directions

### Complementary

Switch actuation	By 30° cam
Positive opening	With
Net weight	0.45 lb(US) (0.205 kg)
Head material	Metal

### Environment

Ambient air temperature for operation	-40...158 °F (-40...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Low temperature

### Packing Units

Package 1 Weight	0.45 lb(US) (0.205 kg)
Package 1 Height	0.041 dm
Package 1 width	0.045 dm
Package 1 Length	0.085 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------