

Ultra Low Loss (ULL) Singlemode MPO12 (Unpinned) to LC, Fiber Extension Cable Assembly, 12-Fiber, Low Smoke Zero Halogen

Product Classification

Regional Availability	Asia Australia/New Zealand Europe Latin America Middle East /Africa North America
Portfolio	CommScope®
Product Type	Fiber array cable assembly
Product Brand	SYSTIMAX ULL
Ordering Note	For additional jacket colors, please contact a CommScope Sales Representative For lengths greater than 999 ft (304 m), orders must be in meters Minimum length may vary based on cable configuration

General Specifications

Color, boot A	Black
Color, boot B	Blue
Color, connector A	Green
Color, connector B	Blue
Construction Type	Stranded
Fibers per Subunit, quantity	12
Furcation Color	Yellow
Interface, Connector A	MPO-12/APC
Interface, Connector B	LC/UPC
Jacket Color	Yellow
Polarity	Method B Enhanced (ULL)
Total Fibers, quantity	12


Dimensions

Breakout Length	33 in
-----------------	-------

URGMPLCGD

Cable Assembly Length Range (m)	1 – 305
Cable Assembly Length Range (ft)	10 – 999

Ordering Tree



Mechanical Specifications

Cable Retention Strength, maximum	11.24 lb @ 0 ° 4.40 lb @ 90 °
-----------------------------------	---------------------------------

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	G.657.A2, TeraSPEED®

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Indoor Low Smoke Zero Halogen (LSZH)

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



Included Products

URGMPLCGD

- 760237972 – Low Smoke Zero Halogen Riser Light Duty MPO Patchcord Cable, 12
N-012-MP-8G1-F30YL/D fiber
- 860637434 – TeraSPEED® Elite LC Connector for 1.6 mm Fiber, single-mode
- 860638318 – MPO12, ULTRA LOW LOSS, FEMALE, SM, GREEN, 3mm