

BIBS6004, Single Sided Four Conductor Clear Insulated Multi-Tap Connector

By Burndy Catalog # BIBS6004

Aluminum Multiple Tap Connector, Clear Insulated, 4 Port, 1 Sided Entry, 4 AWG-600 kcmil, Al/Cu Rated.

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

General

BIBS6004 Catalog Number Connector Type Multi Tap **EU RoHS Indicator** Yes Hex Key 3/8 Insulation Insulation Type Plastisol Aluminum Material Number Of Ports Physical Attribute - Number of Screws Physical Attribute - Screw Type Allen

Plated N
Plating Type Unplated
Sub Brand UNITAP
Temperature Rating 194
Trade Name UNITAP™
Type BIBS, Multi-Port
UPC 781810224113

 Type
 BIBS, Multi-Port

 UPC
 781810224113

 UPC 12 Digit
 7818102241133

Dimensions

Dimension - Height inch 2.75 in
Dimension - Height mm 70 mm
Dimension - L Length Overall 134 mm

mm

Dimension - Length Overall 5.28 in

inch



| Dimension - Width inch | 2.38 in |
|------------------------|---------|
| Dimension - Width mm | 60 mm |

Electrical Ratings

| Operating Voltage | 600 V |
|-------------------|-------|
| Voltage - Maximum | 600 V |

Conductor Related

Conductor - AL Str Size Range 4 AWG - 600 kcmil
Conductor - Copper Str Size 4 AWG - 600 kcmil
Range
Conductor Size 4 AWG-600 KCMIL
Conductor Type • AL C Str-Size

Certifications And Compliance

| Buy America(n) Qualified | TAA Compliant (All status valid till December 2024) |
|----------------------------------|---|
| Buy American Compliant | No |
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Listed Direct | No |
| Burial | |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL 486A-486B |
| Standards - Industry Standards | UL 486A-486B |
| Met | |
| Standards - RoHS Compliance | CM |
| Status | |
| UL Listed | Yes |

CU C Str-Size

Logistics

Minimum Pack Quantity 1


Product Assets

3D Models - BIBS6004_MODEL-IGES
3D Models - BIBS6004_MODEL-STEP
3D Models - BIBS6004_MODEL-PDF
Catalogs - BURNDY Master Catalog - Section A - Mechanical

Catalogs - BORNDT Master Catalog - Section A - Mechanica

Catalogs - UNITAP™ Products

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_BIBS_Lineart Sales Drawings - sc210991-14 Specifications - BIBS6004



©2025 Hubbell Incorporated. All rights reserved BRDY-BIBS6004-SPEC-EN | REV 1/2025