



## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKS
Associated body	ZCKSD35 ZCKS5 ZCKS9H29 ZCKSD37 ZCKS7H29 ZCKSD37H29 ZCKS5H29 ZCKS9 ZCKSD31H29 ZCKS6 ZCKS8H29 ZCKS6H29 ZCKSD39 ZCKSD31 ZCKSD39H29 ZCKS7 ZCKS1 ZCKS1H29 ZCKS2 ZCKS2H29 ZCKSD35H29 ZCKS8
Movement of operating head	Rotary
Type of operator	Roller lever spring return elastomer roller diameter 50 mm)
Type of approach	Lateral approach, 2 directions

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

## Complementary

Switch actuation	By 30° cam
Positive opening	Without
Head material	Plastic

## Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.02 oz (114 g)
Package 1 Height	2.36 in (6 cm)
Package 1 width	2.76 in (7 cm)
Package 1 Length	4.72 in (12 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Weight	5.71 lb(US) (2.59 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------