

Champ VMVL LED luminaires

3,000 to 13,000 lumens

Cl. I, Div. 2, Groups A, B, C, D
Cl. I, Zone 2, AEx ec mb IICT^AGC
Cl. II, Groups E, F, G
Cl. III & Simultaneous Presence
Zone 21 tb IIIC

UL/CSA Listed
IEC/ATEX
Wet Locations
Type 4X; IP66

2L

2L

The Champ VMVL LED family

Champ® VMVL LED luminaires are engineered to provide maintenance-free illumination in the most demanding hazardous rated environments.

The Champ VMVL features a compact, high efficacy design with custom optics to ensure maximum efficiency and mounting flexibility, including the ability to retrofit the Crouse-Hinds installed base to service both LED upgrades and new projects.

Model	Nominal lumens ^B	Watts	Efficacy	Equivalent HID luminaire
VMVL-3	3,250	28	123 lm/W	70W
VMVL-5	5,537	45	127 lm/W	100W
VMVL-7	7,442	61	127 lm/W	175W
VMVL-9	9,234	76	126 lm/W	250W
VMVL-11	11,114	92	122 lm/W	320W
VMVL-13	13,100	95	125 lm/W	400W

Applications:

- For areas with mounting heights of up to 30 feet
- Oil and gas refineries, drilling rigs, petrochemical facilities, food and beverage facilities, platforms, loading docks, tunnels, indoor/outdoor spotlighting, outdoor wall and stanchion mounted general area lighting, and where flammable vapors, gases, ignitable dusts, fibers or flyings are present
- Locations requiring continuous and consistent light levels in extreme ambient temperatures
- Extremely corrosive, wet, dusty, hot and/or cold conditions
- Classified and hazardous locations

Features:

- Instant illumination and restrike
- Cold temperature operation/no warm-up required
- Option for redundancy in drivers with multiple series circuits connected to each driver to avoid complete loss of illumination
- Easy installation – compact modular fixture attaches onto existing Champ mounting module
- Energy-efficient technology – up to 77% energy savings over HID fixtures
- Contains no mercury or other hazardous substances
- Shock- and vibration-resistant solid state luminaires have no filaments or glass components that could break – greatly reduces the risk of premature failure
- Operating ambient: -40°C to 65°C
- Up to 60,000 hours lifetime at 55°C
- 5 year fixture warranty

^A IEC/ATEX certifications applicable for voltage ranges: 100-277 VAC, 127-250 VDC.

^B Nominal lumens based on Type V optics, 5000K CCT with clear glass lens. Wattage measured at 120 VAC.

^C Refer to www.designlights.org Qualified Products List under family models for full listing details. Not all models are approved for all application categories.

^D Custom optics not available with colored LEDs.

Certifications and compliances:

NEC/CEC/IEC:

- Class I, Division 2, Groups A, B, C, D
- Class I, Zone 2, AEx ec mb IICT^AGC
- Class II, Groups E, F, G
- Class III
- Zone 21 tb IIIC
- Simultaneous Presence
- Wet locations, Type 4X, IP66

UL standards:

- UL844 – Hazardous (Classified)
- UL1598 – Luminaires
- UL1598A – Marine

CSA standard:

- CSA C22.2 No. 137

IEC/ATEX standards^A:

- IEC 60079-0:2011, 6th Edition / EN 60079-0:2012
- IEC 60079-7:2010, 5.1 Edition / EN 60079-7:2015
- IEC 60079-31:2008, 2nd Edition / EN 60079-31:2014
- IEC 60529:2001 / EN 60529:2001
- IEC 60598-1:2008 / EN 60598-1:2008
- IEC 60598-2:2008 / EN 60598-2:2008
- IEC 60079-18:2017, 4.1 Edition / EN 60079-18:2015 + A1:2017

Luminaire markings:

- IECEx UL 13.0052X
- DEMKO 13 ATEX 1305741X
- DEMKO 13 ATEX 1475031X

100-277 VAC/127-250 VDC (UNV1 luminaire only)

- II 3 G EX ec mb IIC T5 Gc -40°C to +40°C
- II 3 G EX ec mb IIC T5 Gc -40°C to +55°C
- II 3 G EX ec mb IIC T4 Gc -40°C to +65°C
- II 2 D EX tb IIIC T72°C Db -40°C to +40°C
- II 2 D EX tb IIIC T87°C Db -40°C to +55°C
- II 2 D EX tb IIIC T92°C Db -40°C to +65°C

Qualifications and compliances:

- DesignLights Consortium® Qualified (pending) ^C



Standard materials:

- Lamp housing and adapter – die cast aluminum with Corro-free epoxy powder coat
- Lens – heat- and impact-resistant glass
- Gaskets – silicone
- External hardware – stainless steel
- Factory sealed, no external seals required

LED system:

- High intensity discrete power emitters
- Cool white (5000K, 70 CRI) (standard); warm white (3000K, 80 CRI) or neutral white (4000K, 70 CRI) (optional)
- Custom Type I, III and V optics available

Colored LED options:

- Available in green and amber ^D
- Reduction in light pollution for night space observation and sky glow due to isolating blue wavelength in red and amber colors
- Wildlife-friendly
- Improves visibility for telescopes in observatories during night sky space exploration

Net luminaire weights:

Model	Lbs.	Kg.
VMVL-3 to VMVL-7	19.00	8.62
VMVL-9 to VMVL-13	19.20	8.70
Add mounting modules:		
Pendant	1.25	0.57
Cone pendant	4.00	1.81
Flexible pendant	1.50	0.68
Ceiling	2.75	1.25
Wall	4.50	2.04
Angled stanchion	3.50	1.59
Straight stanchion	4.50	2.04

Champ VMVL LED luminaires

3,000 to 13,000 lumens

Cl. I, Div. 2, Groups A, B, C, D
Cl. I, Zone 2, AEx ec mb IICT●GC
Cl. II, Groups E, F, G
Cl. III & Simultaneous Presence
Zone 21 tb IIIC


UL/cUL Listed
IEC/ATEX
Wet Locations
Type 4X; IP66

2L

2L

Custom optics:

Three optical options to maximize light distribution and intensity:




TYPE I

Long and rectangular for hallways, walkways, loading docks, catwalks.

Ideal for:

- Mining conveyor belts
- Aisleways and hallways
- Catwalks and walkways
- Ramps and loading docks
- Tunnels with overhead mounts




TYPE III

Stanchion and wall mount light distribution, minimizing spillover on the wall.

Ideal for:

- Narrow crosswalks or passages with wall mounted fixtures
- Tunnels with wall mount
- Wall or stanchion mount requiring 180° forward throw beam patterns



TYPE V

Regular circular distribution pattern for high/low bay indoor and outdoor ceiling or pendant mount lighting.

Ideal for:

- Pendant, ceiling or stanchion mount overhead building mounts
- Processing mills, industrial plants, large buildings, warehouses, etc.

● IEC/ATEX certifications applicable for voltage ranges: 100-277 VAC, 127-250 VDC.

Champ VMVL LED luminaires

3,000 to 13,000 lumens

Cl. I, Div. 2, Groups A, B, C, D
Cl. I, Zone 2, AEx ec mb IICT GC
Cl. II, Groups E, F, G
Cl. III & Simultaneous Presence
Zone 21 tb IIIC

UL/cUL Listed
IEC/ATEX
Wet Locations
Type 4X; IP66

2L

2L

Electrical ratings:

UNV1 driver	Input power (watts)	Input amps at 100-277 VAC	UNV34 driver	Input power (watts)	Input amps at 347-480 VAC
VMVL-3	27	0.27 - 0.10	VMVL-3	28	0.08 - 0.06
VMVL-5	45	0.45 - 0.16	VMVL-5	44	0.13 - 0.09
VMVL-7	61	0.61 - 0.21	VMVL-7	57	0.16 - 0.12
VMVL-7-S892	60	0.60 - 0.23	VMVL-7-S892	61	0.18 - 0.13
VMVL-9	76	0.76 - 0.26	VMVL-9	68	0.20 - 0.14
VMVL-9-S892	80	0.80 - 0.29	VMVL-9-S892	73	0.22 - 0.15
VMVL-11	92	0.92 - 0.32	VMVL-11	83	0.24 - 0.17
VMVL-11-S892	97	0.97 - 0.35	VMVL-11-S892	86	0.25 - 0.18
VMVL-13	95	1.10 - 0.42	VMVL-13	91	0.29 - 0.17
VMVL-13-S892	99	1.10 - 0.36	VMVL-13-S892	96	0.31 - 0.19

All models

Power factor	≥0.90	THD	≤15%
--------------	-------	-----	------

UNV1

Voltage range, VAC	100-277V at 50/60 Hz
--------------------	----------------------

Voltage range, VDC	127-250V
--------------------	----------

UNV34

Voltage range, VAC	347-480V at 50/60 Hz
--------------------	----------------------

EMC / CE compliance:

If the dimming interface of the LED driver is connected to an external dimmer which is not provided with the luminaire, a ferrite core must be used on the input and dimming lines.

Approved ferrite cores are: Fair-Rite P/N 0431167281.

Temperature performance data – UNV1 driver:

UNV1: VMVL-3 to VMVL-11	40°C	55°C	65°C
Class I, Division 2	T5	T5	T4A
Class II, Division 1	T6	T6	T4A
Simultaneous rating Class I, Divisions 1 & 2	T4A	T4	T3C
Class I, Zone 2 AEx ec mb; Ex ec mb	T5	T5	T4
Class III, Division 1 Class II, Division 1, Groups E, F, G Zone 21, AEx tb IIIC	T72	T87	T92

UNV1: VMVL-7, -9 & -11-S892	40°C	55°C	65°C
Class I, Division 2	T5	T4A	T4A
Class II, Division 1	T6	T6	T5
Simultaneous rating Class I, Divisions 1 & 2	T4A	T4	T3C
Class I, Zone 2 AEx ec mb; Ex ec mb	T4	T4	T4
Class III, Division 1 Class II, Division 1, Groups E, F, G Zone 21, AEx tb IIIC	T72	T87	T92

UNV1: VMVL-13	40°C	55°C
Class I, Division 2	T4A	T4A
Class II, Division 1	T6	T6
Simultaneous rating Class I, Divisions 1 & 2	T4A	T4A
Class I, Zone 2 AEx ec mb; Ex ec mb	T5	T4
Class III, Division 1 Class II, Division 1, Groups E, F, G Zone 21, AEx tb IIIC	T64	T77

UNV1: VMVL-13-S892	40°C	55°C
Class I, Division 2	T5	T4A
Class II, Division 1	T6	T6
Simultaneous rating Class I, Divisions 1 & 2	T5	T4A
Class I, Zone 2 AEx ec mb; Ex ec mb	T4	T4
Class III, Division 1 Class II, Division 1, Groups E, F, G Zone 21, AEx tb IIIC	T64	T77

Temperature performance data – UNV34 driver:

UNV34: VMVL-3 to VMVL-11	40°C	55°C	65°C
Class I, Division 2	T5	T5	T4A
Class II, Division 1	T6	T6	T5
Simultaneous rating Class I, Divisions 1 & 2	T4A	T4	T3C

UNV34: VMVL-7, -9, & -11-S892	40°C	55°C	65°C
Class I, Division 2	T5	T5	T4A
Class II, Division 1	T6	T6	T5
Simultaneous rating Class I, Divisions 1 & 2	T4A	T4	T3C

UNV34: VMVL-13	40°C	55°C
Class I, Division 2	T4A	T4A
Class II, Division 1	T6	T6
Simultaneous rating Class I, Divisions 1 & 2	T4A	T4A

UNV34: VMVL-13-S892	40°C	55°C
Class I, Division 2	T4A	T4A
Class II, Division 1	T6	T6
Simultaneous rating Class I, Divisions 1 & 2	T4A	T4A

Ⓘ IEC/ATEX certifications applicable for voltage ranges: 100-277 VAC, 127-250 VDC.

Ⓙ IEC voltage: 100-240 VAC at 50/60 Hz. For VMVL-3: PF>0.9 from 100-255 VAC.

Ⓚ T-code is T4A for VMVL-11 with R1, R3 optics.

Ⓛ T-code is T4A for VMVL-11-S892 with R1, R3 optics.

Ⓜ T-code is T4 for R1, R3 optics.

Champ VMVL LED luminaires

3,000 to 13,000 lumens

Cl. I, Div. 2, Groups A, B, C, D
Cl. I, Zone 2, AEx ec mb IICT[Ⓚ]GC
Cl. II, Groups E, F, G
Cl. III & Simultaneous Presence
Zone 21 tb IIIC

UL/cUL Listed
IEC/ATEX
Wet Locations
Type 4X; IP66

2L

Ordering information:

Part number example

VMVL-3-N-2A-R1-G-UNV1-S831-S891-UPLT

VMVL -3 -N -2A -R1 -G -UNV1 -S831 -S891 -UPLT

Light source / intensity

3	3,250 nominal lumens
5	5,537 nominal lumens
7	7,442 nominal lumens
9	9,234 nominal lumens
11	11,114 nominal lumens
13[Ⓛ]	13,100 nominal lumens
A	Amber – 5,200 lumens
G	Green – 4,300 lumens

Color temperature

BLANK	Cool white (5000K), 70 CRI
N[Ⓜ]	Neutral white (4000K), 70 CRI
W	Warm white (3000K), 80 CRI

Mounting style

BLANK	No mounting module	2C	¾" ceiling
J	1½" stanchion, 25° angled	3C	1" ceiling
P	1½" stanchion, straight	20C	20mm ceiling
2A	¾" pendant	25C	25mm ceiling
3A	1" pendant	2HA	¾" flexible pendant
20A	20mm pendant	2TW	¾" wall
25A	25mm pendant	3TW	1" wall
2B	¾" cone pendant	20TW	20mm wall
3B	1" cone pendant	25TW	25mm wall

Guard

BLANK	No guard
G	Wire guard

Voltage[Ⓚ]

UNV1	100-277 VAC, 50/60 Hz; 127-250 VDC
UNV34	347-480 VAC, 50/60 Hz

Optics

BLANK	Type V optic standard
R1	Type I optic (<i>all mounts minus ceiling</i>)
R1A[Ⓝ]	Type I optic (<i>ceiling with conduit 45° counterclockwise from top hat hinge</i>)
R1B[Ⓝ]	Type I optic (<i>ceiling with conduit 135° clockwise from top hat hinge</i>)
R3	Type III optic (<i>all mounts minus ceiling</i>)
R3AP[Ⓝ]	Type III optic (<i>select when using Appleton® top hat adapter with Champ fixture</i>)
R3A1[Ⓝ]	Type III optic (<i>ceiling with conduit 45° counterclockwise from top hat hinge</i>)
R3A2[Ⓝ]	Type III optic (<i>ceiling with conduit 135° clockwise from top hat hinge</i>)
R3B1[Ⓝ]	Type III optic (<i>ceiling with conduit 45° clockwise from top hat hinge</i>)
R3B2[Ⓝ]	Type III optic (<i>ceiling with conduit 135° counterclockwise from top hat hinge</i>)

Lens material

BLANK	Clear glass
S891	Diffused glass
S896[Ⓡ]	Teflon coated lens
S903	Polycarbonate
UPLT[Ⓢ]	Uplight refractor lens

Accessories and options[Ⓚ]

S812[Ⓝ]	Trunnion mount kit with pin
S831	Safety cable
S890	Quick Clip
S891	Diffused lens
S892[Ⓚ]	Redundant driver
TB6[Ⓢ]	Six-pole terminal block

[Ⓚ] IEC/ATEX certifications applicable for voltage ranges: 100-277 VAC, 127-250 VDC.

[Ⓛ] For 13L models, add suffix -M2 at the end of the part number. Example: VMVL-13-2A-R1-UNV1-S831-M2.

[Ⓜ] Consult factory for lead time. 5700K and 6500K are available upon request; consult factory. Not available for amber or green LED.

[Ⓝ] Available with ceiling mount modules only.

[Ⓚ] IEC voltage: 100-240 VAC at 50/60 Hz.

[Ⓟ] Ordered with fixture or available separately.

[Ⓚ] Available for VMVL-7, -9, -11 and -13 only.

[Ⓡ] For NEC/CEC only.

[Ⓢ] Recommended for use with Type V optic.

Champ VMVL LED luminaires

3,000 to 13,000 lumens

Cl. I, Div. 2, Groups A, B, C, D
Cl. I, Zone 2, AEx ec mb IICT●GC
Cl. II, Groups E, F, G
Cl. III & Simultaneous Presence
Zone 21 tb IIIC

UL/cUL Listed
IEC/ATEX
Wet Locations
Type 4X; IP66

2L

2L

Accessories (ordered separately):

Replacement driver kits

VMVL-3-5-7L-UNV1-DRIVER-KIT	UNV1 replacement driver kit for VMVL-3, -5 and -7
VMVL-9-11L-UNV1-DRIVER-KIT	UNV1 replacement driver kit for VMVL-9 and -11
VMVL-96W-13L-UNV1-M2-DRIVER-REPL-KIT	UNV1 replacement driver kit for VMVL-13
VMVL-3L-5L-UNV34-DRIVER-KIT	UNV34 replacement driver kit for VMVL-3 and -5
VMVL-7L-UNV34-DRIVER-KIT	UNV34 replacement driver kit for VMVL-7
VMVL-9L-UNV34-DRIVER-KIT	UNV34 replacement driver kit for VMVL-9
VMVL-11L-UNV34-DRIVER-KIT	UNV34 replacement driver kit for VMVL-11
VMVL-13-M2-DRIVER-KIT	UNV34 replacement driver kit for VMVL-13
VMVL-7L-S892-UNV1-DRIVER-KIT	UNV1 replacement redundant driver kit for VMVL-7
VMVL-9L-11L-S892-UNV1-DRIVER-KIT	UNV1 replacement redundant driver kit for VMVL-9 and -11
VMVL-13-UNV1-S892-M2-DRIVER-KIT	UNV1 replacement redundant driver kit for VMVL-13
VMVL-7L-S892-UNV34-DRIVER-KIT	UNV34 replacement redundant driver kit for VMVL-7
VMVL-9L-S892-UNV34-DRIVER-KIT	UNV34 replacement redundant driver kit for VMVL-9
VMVL-11L-S892-UNV34-DRIVER-KIT	UNV34 replacement redundant driver kit for VMVL-11
VMVL-13-UNV34-S892-M2-DRIVER-KIT	UNV34 replacement redundant driver kit for VMVL-13
VMVL-AL-GL-UNV1-DRIVER-KIT	UNV1 replacement driver kit for amber or green models

Mounting and hardware

VMVL S812 K1	Trunnion mount kit with pin●
VMVL S812 K1 DBR	PVC coated trunnion mount kit with pin●
VMVL S831 K1	Safety cable
VMVL S890 K1	Quick Clip

Mounting adapters

CHMM1	For Appleton MercMaster III mounts
CHMM2	For MercMaster II mounts
CHMM3	For Thomas & Betts HazLux mounts
CHMM4	For GE H2 Filtr-Gard mounts

Refractor kit

PVML-UPLT-KIT	Uplight refractor lens
---------------	------------------------

Photocells

D2S20	Photocell, 120V
D2S208 277	Photocell, 208-277V

Lens guard

P3001	Wire guard
-------	------------

● IEC/ATEX certifications applicable for voltage ranges: 100-277 VAC, 127-250 VDC.

● Available with ceiling mounted modules only.

Champ VMVL LED luminaires

3,000 to 13,000 lumens

Cl. I, Div. 2, Groups A, B, C, D
Cl. I, Zone 2, AEx ec mb IICT GC
Cl. II, Groups E, F, G
Cl. III & Simultaneous Presence
Zone 21 tb IIIC


UL/cUL Listed
IEC/ATEX
Wet Locations
Type 4X; IP66

2L

Optics options:


R1, R3 and BLANK

Type I, III and V optics with all mounts minus ceiling




R1A and R3A1

Type I and Type III ceiling mount only




R1B and R3B1

Type I and Type III ceiling mount only




R3AP

Type III wall mount




R3A2

Type III ceiling mount only



R3B2

Type III ceiling mount only



IEC/ATEX certifications applicable for voltage ranges: 100-277 VAC, 127-250 VDC.

Champ VMVL LED luminaires

3,000 to 13,000 lumens

Cl. I, Div. 2, Groups A, B, C, D
Cl. I, Zone 2, AEx ec mb IICT^oGC
Cl. II, Groups E, F, G
Cl. III & Simultaneous Presence
Zone 21 tb IIIC


UL/cUL Listed
IEC/ATEX
Wet Locations
Type 4X; IP66

2L


2L

Dimensions:


Stanchion - 25° angled




Stanchion - straight




Pendant




Ceiling




Wall




Cone pendant



Trunnion



Mounting module series:



IEC/ATEX certifications applicable for voltage ranges: 100-277 VAC, 127-250 VDC.