



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Multi-directional head
Product compatibility	XCKJ
Associated body	ZCKJ21 ZCKJ6H7 ZCKJD35H7 ZCKJ11H7 ZCKJ1H7 ZCKJD37 ZCKJD35H29 ZCKJD35 ZCKJ21H7 ZCKJ11 ZCKJD31H29 ZCKJD39 ZCKJD31 ZCKJ7H7 ZCKJ5H7 ZCKJ9 ZCKJ9H7 ZCKJ2H29 ZCKJ21H29 ZCKJD37H7 ZCKJ6 ZCKJ11H29 ZCKJ8H7 ZCKJ1 ZCKJD39H7 ZCKJD37H29 ZCKJ2H7 ZCKJ9H29 ZCKJ5 ZCKJ6H29 ZCKJ7H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ5H29
 ZCKJD39H29
 ZCKJ2
 ZCKJ8H29
 ZCKJD31H7
 ZCKJ1H29
 ZCKJ7
 ZCKJ8

Movement of operating head	Multi-directional
Type of operator	Cat"'s whisker spring return
Type of approach	Multi-directional approach

Complementary

Switch actuation	By any moving part
Positive opening	Without
Net weight	0.25 lb(US) (0.115 kg)
Head material	Metal

Environment

Ambient air temperature for operation	50...248 °F (10...120 °C)
Ambient air temperature for storage	50...248 °F (10...120 °C)
Environmental characteristic	High temperature

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.41 oz (125 g)
Package 1 Height	1.46 in (3.7 cm)
Package 1 width	1.46 in (3.7 cm)
Package 1 Length	6.42 in (16.3 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	24
Package 2 Weight	7.32 lb(US) (3.32 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------