



Main

| | |
|------------------------------|--|
| Range of product | Osiswitch |
| Series name | Classic |
| Product or component type | Limit switch lever |
| Device short name | ZCKY |
| Product compatibility | XCKJ XCKL XCKM XCKS |
| Associated head | ZCKD05 ZCKE05 |
| Type of operator | Spring return roller lever thermoplastic variable length |
| Positive opening | Without |
| Environmental characteristic | Low temperature Standard environment |

Complementary

| | |
|----------------------------|------------------|
| Movement of operating head | Rotary |
| Switch actuation | By 30° cam |
| Type of approach | Lateral approach |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -40...20 °C low temperature -25...70 °C standard environment |
| Ambient air temperature for storage | -25...70 °C standard environment -25...70 °C low temperature |
| RoHS EUR conformity date | 2Q2009 |
| RoHS EUR status | Will be compliant |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.