

ORDERING INFORMATION


Order code: 65493
 Description: F54T5/30K/8/HO/PS/G5/STD
 UPC: 69549654938
 Case quantity: 25




PERFORMANCE DATA

Shape: T5
 Base: G5 (Min Bipin)
 Starting method: Program Start (PS)
 Wattage (W): 54
 Colour temperature (K): 3 000
 CRI: 85
 Rated life on PS/PRS¹ ballast:
 Based on a 3 hour start 24 000
 Based on a 12 hour start 30 000
 Initial lumens (lm): 5 000
 Mean lumens (lm): 4 656
 Nominal efficiency (lm/W): 93
 TCLP compliant: Yes
 Phosphor composition: Triphosphor
 Nominal lamp operating frequency (Hz): 60
² Minimum starting temperature (°C): -10

DIMENSIONS



SPECTRAL DISTRIBUTION



¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

² The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T5 High Output ballast.



OUTDOOR



INDOOR



2 YEARS WARRANTY



TCLP COMPLIANT



RECYCLABLE



ENERGY SAVING



ONE SYSTEM WARRANTY



Means this bulb meets federal minimum efficiency standards.

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

February 21, 2017

STANDARD