

# Technical Information Bulletin

## LED Lamps



Date: \_\_\_\_\_ Name of distributor: \_\_\_\_\_  
 In hands date of project: \_\_\_\_\_ Client #: \_\_\_\_\_  
 Project name/Number: \_\_\_\_\_ Name of end user: \_\_\_\_\_

### ORDERING INFORMATION

Order code: 67958  
 Description: LED/A19/S5/12W/40K/STD  
 UPC: 69549679580  
 Case quantity: 1 / 100



MOL : 4 15/16 in. (125 mm)

Dia. : 2 9/16 in. (65 mm)

### PERFORMANCE DATA

Shape: A19  
 Wattage (W): 12  
 Base: E26  
 Lamp voltage (VAC): 120  
 Colour temperature (K)\*\*: 4 000  
 Life L70 (hrs): 25 000  
 Initial lumens (lm)\*: 1 100  
 Initial lumens per watt (lm/W): 92  
 CRI: 80  
 Beam angle (°): 220  
 Power factor: 0.70  
 Operating temperature range: - 20 °C / - 4 °F to 40 °C / 104 °F

\*Initial lumens range: +/- 10 %      \*\*Typical colour temperature range: +/- 5 %



### CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock – do not use where directly exposed to water or weather.
- Suitable for use in totally enclosed luminaires.
- Suitable for use in damp locations.
- Do not open – no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- For complete dimmer and warranty information visit [www.standardpro.com](http://www.standardpro.com).

### COMPATIBLE DIMMERS

Brand	Model
Lutron	PD-5NE <sup>1</sup> , PD-6WCL, RRD-6NA <sup>2</sup> , DVCL-153P, CTCL-153P, DVCL-253P <sup>3</sup> , DVRP-253, SELV-300P
Leviton	066EV, IPE04-1LZ

<sup>1</sup> Lamp may flicker at low dimming setting  
<sup>2</sup> Power may turn off at low dimming setting  
<sup>3</sup> Dimming range may vary

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Signature: \_\_\_\_\_

Date: \_\_\_\_\_

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications. Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.