



NAME:	
TYPE:	
DATE:	
NOTES:	

**SPECIFICATIONS**

**LIGHT UNIT:** Rugged cast-aluminum, corrosion-resistant housing in dark bronze paint for lasting durability.

An impact resistant poly-carbonate lens features a prismatic design to reduce glare

LED lamp head is isolated from the driver. It is located in the rear housing, promoting a long service life.

The lens is sealed to keep out moisture, dirt and bugs.

Replacement equivalents of a Metal Halide luminaire:  
 - OS1800 = 150W  
 - OS1850 = 250W

LEDs maintain 70% of light output at 100,000 hours of service life.

---

**INSTALLATION:** Easily mounts to a recessed junction box or for a surface mounting, conduit entry ports are offered.  
 - Three(3) conveniently located 1/2" threaded conduit entry ports.

The unit offers a hinged front panel design for hands-free installation.

---

**ELECTRICAL:** Energy efficient LED provides provides high lumen output, with low wattage:  
 - OS1800 = 4050 Lumens / 35 watt  
 - OS1850 = 6150 Lumens / 57 watt

This model is offered with a 120-277V driver.

Rated for outdoor installations, -40°C minimum ambient.


**LISTINGS**  
 UL/cUL and DLC listed Listed to U.S. and Canadian safety standards

COLOR TEMPERATURE:	5k
OPERATING TEMPERATURE:	-40°C + 40°C
CRI:	80+
LUMEN OUTPUT:	6150LM
WATTS:	57W
LED LIFE:	100,000 hours
WARRANTY:	5 years
VOLTAGE:	120-277V
METAL HALIDE EQUIVALENT:	250W

**APPLICATIONS**

The high-performance LED Canopy (garage light) offers security and general lighting for indoor or outdoor commercial applications. With a classic design and latest LED chip, heat sink & driver technology, it is an LED canopy light upgrade made easy.

DIMENSIONS



RATINGS



ORDERING GUIDE

**OS1850 SERIES**

Series	Finish
OS1850LED-CG	DB Dark Bronze
Notes:	Configure product using <b>BOLD</b> options: Ex: <b>OS1850LED-CG-DB</b>