



# Kit 23 PC TiN SHOCKWAVE™

48-89-4631



## What's Included

- (2) 1/16" Titanium SHOCKWAVE™ (48-89-4601)
- (2) 5/64" Titanium SHOCKWAVE™ (48-89-4602)
- (1) 3/32" Titanium SHOCKWAVE™ (48-89-4603)
- (2) 7/64" Titanium SHOCKWAVE™ (48-89-4604)
- (2) 1/8" Titanium SHOCKWAVE™ (48-89-4605)
- (1) 9/64" Titanium SHOCKWAVE™ (48-89-4606)
- (2) 5/32" Titanium SHOCKWAVE™ (48-89-4607)
- (1) 11/64" Titanium SHOCKWAVE™ (48-89-4608)
- (2) 3/16" Titanium SHOCKWAVE™ (48-89-4609)
- (1) 13/64" Titanium SHOCKWAVE™ (48-89-4610)
- (1) 7/32" Titanium SHOCKWAVE™ (48-89-4611)
- (2) 1/4" Titanium SHOCKWAVE™ (48-89-4613)
- (1) 5/16" Titanium SHOCKWAVE™ (48-89-4617)
- (1) 3/8" Titanium SHOCKWAVE™ (48-89-4621)
- (1) 1/2" Titanium SHOCKWAVE™ (48-89-4629)

## Where to Buy

- ☐ Shop Online
- ☐ Find Local

## Features

- Titanium Coating for Up to 3X Life vs. Black Oxide
- SHOCKWAVE™ Impact Duty, Engineered forDrills and Impacts
- RED HELIX™ Design for Rapid Chip Removal™
- CHIP BREAKER™ Decreased Heat Buildup
- 135° split point for precision start no walking

## Overview

Milwaukee® SHOCKWAVE™ Impact Duty Titanium Drill Bits with RED HELIX™ are engineered for impacts and drills. Designed with a Variable Helix ™ with an aggressive 35° Helix Angle which ends at 15°, the Impact Duty Titanium Drill bits with RED HELIX™ provide Rapid Chip Removal™ to limit heat buildup to Stay Sharper Longer™. The 135° split point tip delivers a precision start and prevents walking for fast, accurate holes. Titanium coating can be used in all drilling applications to give you up to 3X life vs. Black Oxide Drill Bits™.

## Specifications

Length	10.39"
--------	--------