

| Project: | | Type: |
|-----------|--------------|-------|
| _ | | Nr |
| Drawn by: | Catalogue #: | Date: |

Individual Spec Sheet

WPS GEN 4 CLASSIC WALL PACK

ORDERING INFORMATION

Order code:

Model number: WPS-NS40-W/40K UPC: 069549016712 **DLC unique ID:** PLVM09BUX07G

Case quantity:

PHYSICAL DATA

Dimensions: 14.37" x 9.33" x 7.36" (365 mm x 237 mm x 187 mm)

Housing material: Aluminium die-cast

Lens Material: Prismatic tempered glass lens

PERFORMANCE DATA

Watts (W): 40 Volts (VAC): 120-277 Colour temperature (K)1: 4 000 Lumen output (Im)2: 6 004 Efficiency (Im/W): 142 CRI: >80 Finish: Bronze Photocell: No Dimming (Yes/No): Yes LED current (mA) 354 Power factor: 0.90 THD (%):

Operating temp. range: -40°C to 50°C

COMPATIBLE ACCESSORIES

| Order code | Description | |
|------------|----------------------------|--|
| 68370 | 18" Bronze metal backplate | |
| 68371 | Bronze glareshield | |
| 68372 | Stainless Steel wireguard | |









fixture















Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.


This lighting equipment complies with Canadian standard ICES-005 for use in residential applications. Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



 $^{^1}$ Typical colour temperature range: +/- 5 % 2 Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %



DIMENSIONS



| Qty | Description | Price |
|------------------------|--|-------|
| | | |
| Name: | ations of the luminaire configuration mentioned above. | |
| Company: Signature: | | |
| Signature: | | Date: |
| | | |

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

