


ZCKL1H7

limit switch body ZCKL - without display - 1 NO
+ 1 NC - fixed - metal



Main

Range of product	Osiswitch
Series name	Classic
Product or component type	Limit switch body
Device short name	ZCKL
Body type	Fixed
Product compatibility	XCKL
Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.34...2 x 1.5 mm ²
Cable entry	1 entry tapped for 1/2" NPT cable gland
Number of poles	2
Contacts type and composition	1 NO + 1 NC
Contacts operation	Snap action
Positive opening	With
Ambient air temperature for operation	-25...70 °C standard environment
Environmental characteristic	Standard environment

Complementary

Associated head	ZCKD02 ZCKD05 ZCKD06 ZCKD08 ZCKD10 ZCKD109 ZCKD15 ZCKD16 ZCKD17 ZCKD21 ZCKD219 ZCKD23 ZCKD239 ZCKD29 ZCKD41 ZCKD59 ZCKD81 ZCKD91
Body material	Metal
Number of steps	1
Contacts material	Silver plated contacts
Minimum actuation speed	0,01 m/min
Contact code designation	A300 AC-15 240 V 3 A 10 A EN/IEC 60947-5-1 appendix A Q300 DC-13 250 V 0,27 A EN/IEC 60947-5-1 appendix A
[Ui] rated insulation voltage	300 V UL 508 contact block 300 V CSA 22-2 No 14 contact block 500 V 3 IEC 60947-1 contact block
Resistance across terminals	0,25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-1 6 kV IEC 60664
Short circuit protection	10 A cartridge fuse gG
Electrical durability	5000000 cycles DC-13 48 V 7 W IEC 60947-5-1 appendix C < 60 cyc/mn 0,5 5000000 cycles DC-13 120 V 4 W IEC 60947-5-1 appendix C < 60 cyc/mn 0,5 5000000 cycles DC-13 24 V 10 W IEC 60947-5-1 appendix C < 60 cyc/mn 0,5
Product weight	0,21 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IP degree of protection	IP65
IK degree of protection	IK08
Ambient air temperature for storage	-40...70 °C
RoHS EUR conformity date	2Q2009
RoHS EUR status	Will be compliant