


BSH0703T31F1A

AC servo motor BSH - 2.83 N.m - 6000 rpm -
keyed shaft - with brake - IP65



Main

Product or component type	Servo motor
Device short name	BSH
Maximum mechanical speed	8000 rpm
Continuous stall torque	24.78 Lbf.In (2.8 N.m) LXM05AD28M2, 200...240 V, single phase 24.78 Lbf.In (2.8 N.m) LXM05BD28M2, 200...240 V, single phase 24.78 Lbf.In (2.8 N.m) LXM05CD28M2, 200...240 V, single phase 23.01 Lbf.In (2.6 N.m) LXM32.D18M2 6 A, 230 V, single phase 25.05 Lbf.In (2.83 N.m) LXM15LD28M3, 230 V, three phase 24.78 Lbf.In (2.8 N.m) LXM05AD28F1, 110...120 V, single phase 24.78 Lbf.In (2.8 N.m) LXM05AD42M3X, 200...240 V, three phase 24.78 Lbf.In (2.8 N.m) LXM05BD28F1, 110...120 V, single phase 24.78 Lbf.In (2.8 N.m) LXM05BD42M3X, 200...240 V, three phase 24.78 Lbf.In (2.8 N.m) LXM05CD28F1, 110...120 V, single phase 24.78 lbf.in (2.8 N.m) LXM05CD42M3X, 200...240 V, three phase
Peak stall torque	65.32 Lbf.In (7.38 N.m) LXM05AD28F1, 110...120 V, single phase 65.32 Lbf.In (7.38 N.m) LXM05AD28M2, 200...240 V, single phase 65.32 Lbf.In (7.38 N.m) LXM05BD28F1, 110...120 V, single phase 65.32 Lbf.In (7.38 N.m) LXM05BD28M2, 200...240 V, single phase 65.32 Lbf.In (7.38 N.m) LXM05CD28F1, 110...120 V, single phase 65.32 Lbf.In (7.38 N.m) LXM05CD28M2, 200...240 V, single phase 65.50 Lbf.In (7.4 N.m) LXM32.D18M2 6 A, 230 V, single phase 65.32 Lbf.In (7.38 N.m) LXM15LD28M3, 230 V, three phase 90.72 Lbf.In (10.25 N.m) LXM05AD42M3X, 200...240 V, three phase 90.72 Lbf.In (10.25 N.m) LXM05BD42M3X, 200...240 V, three phase 90.72 lbf.in (10.25 N.m) LXM05CD42M3X, 200...240 V, three phase
Nominal output power	750 W LXM05AD28M2, 200...240 V, single phase 750 W LXM05BD28M2, 200...240 V, single phase 750 W LXM05CD28M2, 200...240 V, single phase 750 W LXM05AD28F1, 110...120 V, single phase 750 W LXM05BD28F1, 110...120 V, single phase 750 W LXM05CD28F1, 110...120 V, single phase 900 W LXM32.D18M2 6 A, 230 V, single phase 1250 W LXM15LD28M3, 230 V, three phase 750 W LXM05AD42M3X, 200...240 V, three phase 750 W LXM05BD42M3X, 200...240 V, three phase 750 W LXM05CD42M3X, 200...240 V, three phase

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Nominal torque	21.24 Lbf.In (2.4 N.m) LXM05AD28M2, 200...240 V, single phase 21.24 Lbf.In (2.4 N.m) LXM05BD28M2, 200...240 V, single phase 21.24 Lbf.In (2.4 N.m) LXM05CD28M2, 200...240 V, single phase 21.24 Lbf.In (2.4 N.m) LXM05AD28F1, 110...120 V, single phase 21.24 Lbf.In (2.4 N.m) LXM05BD28F1, 110...120 V, single phase 21.24 Lbf.In (2.4 N.m) LXM05CD28F1, 110...120 V, single phase 18.59 Lbf.In (2.1 N.m) LXM32.D18M2 6 A, 230 V, single phase 17.70 Lbf.In (2 N.m) LXM15LD28M3, 230 V, three phase 21.24 Lbf.In (2.4 N.m) LXM05AD42M3X, 200...240 V, three phase 21.24 Lbf.In (2.4 N.m) LXM05BD42M3X, 200...240 V, three phase 21.24 lbf.in (2.4 N.m) LXM05CD42M3X, 200...240 V, three phase
Nominal speed	3000 rpm LXM05AD28M2, 200...240 V, single phase 3000 rpm LXM05BD28M2, 200...240 V, single phase 3000 rpm LXM05CD28M2, 200...240 V, single phase 3000 rpm LXM05AD42M3X, 200...240 V, three phase 3000 rpm LXM05BD42M3X, 200...240 V, three phase 3000 rpm LXM05CD42M3X, 200...240 V, three phase 3000 rpm LXM05AD28F1, 110...120 V, single phase 3000 rpm LXM05BD28F1, 110...120 V, single phase 3000 rpm LXM05CD28F1, 110...120 V, single phase 4000 rpm LXM32.D18M2 6 A, 230 V, single phase 6000 rpm LXM15LD28M3, 230 V, three phase
Product compatibility	LXM05AD28F1 110...120 V single phase LXM05AD28M2 200...240 V single phase LXM05BD28F1 110...120 V single phase LXM05BD28M2 200...240 V single phase LXM05CD28F1 110...120 V single phase LXM05CD28M2 200...240 V single phase LXM32.D18M2 230 V single phase LXM05AD42M3X 200...240 V three phase LXM05BD42M3X 200...240 V three phase LXM05CD42M3X 200...240 V three phase LXM15LD28M3 230 V three phase
Shaft end	Keyed
IP degree of protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	131072 points/turn
Holding brake	With
Mounting support	International standard flange
Electrical connection	Straight connectors

Complementary

Range compatibility	Lexium 32 Lexium 15 Lexium 05
Supply voltage max	480 V
Phase	Three phase
Continuous stall current	7 A
Maximum continuous power	1.7 W

Maximum current Irms	18 A LXM32.D18M2 30.9 A LXM15LD28M3 29.2 A LXM05AD28F1 29.2 A LXM05AD28M2 29.2 A LXM05AD42M3X 29.2 A LXM05BD28F1 29.2 A LXM05BD28M2 29.2 A LXM05BD42M3X 29.2 A LXM05CD28F1 29.2 A LXM05CD28M2 29.2 A LXM05CD42M3X
Maximum permanent current	29.2 A
Switching frequency	8 kHz
Second shaft	Without second shaft end
Shaft diameter	0.55 in (14 mm)
Shaft length	1.18 in (30 mm)
Key width	0.79 in (20 mm)
Feedback type	Single turn SinCos Hiperface
Holding torque	26.55 lbf.in (3 N.m) holding brake
Motor flange size	2.76 in (70 mm)
Number of motor stacks	3
Torque constant	0.44 N.m/A 248 °F (120 °C)
Back emf constant	29 V/krpm 248 °F (120 °C)
Number of motor poles	6
Rotor inertia	0.81 kg.cm ²
Stator resistance	0.91 Ohm 68 °F (20 °C)
Stator inductance	4.4 mH 68 °F (20 °C)
Stator electrical time constant	4.84 ms 68 °F (20 °C)
Maximum radial force Fr	400 N 6000 rpm 430 N 5000 rpm 460 N 4000 rpm 510 N 3000 rpm 580 N 2000 rpm 730 N 1000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	12 W
Type of cooling	Natural convection
Length	10.00 in (254 mm)
Centring collar diameter	2.36 in (60 mm)
Centring collar depth	0.10 in (2.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.22 in (5.5 mm)
Circle diameter of the mounting holes	3.23 in (82 mm)
Net weight	8.38 lb(US) (3.8 kg)

Ordering and shipping details

Category	18282 - LEXIUM 32 MOTORS
Discount Schedule	PC53
GTIN	03389118137707
Nbr. of units in pkg.	1
Package weight(Lbs)	8.9 lb(US) (4.04 kg)
Returnability	No
Country of origin	DE


Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.84 in (12.3 cm)
Package 1 width	5.04 in (12.8 cm)
Package 1 Length	14.84 in (37.7 cm)

Contractual warranty

Warranty	18 months
----------	-----------

Example with Straight Connectors




Straight connectors		Rotatable angled connectors		c (without brake)	c (with brake)	c1	c2	c3	h	h1	Ø	Ø1 for screws
b1	b2	b1	b2									
39.5	25.5	39.5	39.5	220	254	30	20	5	5 N9	3 ^{+0.1} ₀	14 k6	M5 x 12.5

Straight connectors		Rotatable angled connectors		c (without brake)	c (with brake)	c1	c2	c3	h	h1	Ø	Ø1 for screws
b1	b2	b1	b2									
1.55	1.00	1.55	1.55	8.66	10.00	1.18	0.78	0.19	0.20 N9	$0.12^{+0.004}_0$	0.55 k6	M5 x 0.49

230 V Single-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32•D18M2 servo drive



- X Speed in rpm
- Y Torque in Nm
- 1 Peak torque
- 2 Continuous torque