9001KP5

30mm push button, Type K, pilot light, transformer light module, 380/400VAC 50/60Hz, no lens, NEMA 4, 13





Main

IVIAIII	
Range of Product	Harmony 9001K
Product or Component Type	Head for pilot light
Device short name	К

Complementary

Mounting diameter 1.18 in (30 mm) Cap/operator or lens colour Without cap Bulb base BA 9s Light block supply Via transformer 380 V AC 50/60 Hz Via transformer 480 V AC 50/60 Hz Shape of screw head Round Light source Incandescent bulb Operating Mode Normal [Us] rated supply voltage 380480 V Light block supply Via integral transformer Supply frequency 5060 Hz Size 30 mm	Bezel material	Metal	
Bulb base BA 9s Light block supply Via transformer 380 V AC 50/60 Hz Via transformer 480 V AC 50/60 Hz Shape of screw head Round Light source Incandescent bulb Operating Mode Normal [Us] rated supply voltage 380480 V Light block supply Via integral transformer Supply frequency 5060 Hz	Mounting diameter	1.18 in (30 mm)	
Light block supply Via transformer 380 V AC 50/60 Hz Via transformer 480 V AC 50/60 Hz Shape of screw head Round Light source Incandescent bulb Operating Mode Normal [Us] rated supply voltage 380480 V Light block supply Via integral transformer Supply frequency 5060 Hz	Cap/operator or lens colour	Without cap	
Via transformer 480 V AC 50/60 Hz Shape of screw head Round Light source Incandescent bulb Operating Mode Normal [Us] rated supply voltage 380480 V Light block supply Via integral transformer Supply frequency 5060 Hz	Bulb base	BA 9s	
Light source Incandescent bulb Operating Mode Normal [Us] rated supply voltage 380480 V Light block supply Via integral transformer Supply frequency 5060 Hz	Light block supply		
Operating Mode Normal [Us] rated supply voltage 380480 V Light block supply Via integral transformer Supply frequency 5060 Hz	Shape of screw head	Round	
[Us] rated supply voltage 380480 V Light block supply Via integral transformer Supply frequency 5060 Hz	Light source	Incandescent bulb	
Light block supply Via integral transformer Supply frequency 5060 Hz	Operating Mode	Normal	
Supply frequency 5060 Hz	[Us] rated supply voltage	380480 V	
	Light block supply	Via integral transformer	
Size 30 mm	Supply frequency	5060 Hz	
020	Size	30 mm	

Environment

Product Certifications	CE[RETURN]CSA LR25490 class 3211 03[RETURN]UL listed file E42259 CCN NKCR
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

Ordering and shipping details

Category	21426-9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	785901005704
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.90 in (4.826 cm)	
Package 1 Width	2.30 in (5.842 cm)	
Package 1 Length	3.70 in (9.398 cm)	
Package 1 Weight	8.00 oz (226.796 g)	

Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
☑ REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
China RoHS Declaration
€Yes
Product Environmental Profile
No need of specific recycling operations
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months