
FEXLCSC42



OM4 LC to SC, Fiber Patch Cord, 1.6 mm Duplex, Riser

Product Classification

Regional Availability

Asia | Australia/New Zealand | Europe | Latin America | Middle East

/Africa | North America

Portfolio CommScope®

Product Type Fiber patch cord, duplex

Product Brand SYSTIMAX InstaPATCH® 360

Ordering Note For lengths greater than 999 ft (304 m), orders must be in meters | Minimum length

may vary based on cable configuration

General Specifications

Color, boot AAquaColor, boot BAquaColor, connector ABeigeColor, connector BBeigeInterface, Connector ALC/UPCInterface, Connector BSC/UPCJacket ColorAqua

Polarity Method B

Total Fibers, quantity 2

Dimensions


Cable Assembly Length, minimum (ft) 2
Cable Assembly Length, maximum (ft) 325
Cable Assembly Length, minimum (m) 1
Cable Assembly Length, maximum (m) 99

Diameter Over Jacket 1.6 mm | 0.063 in

COMMSCOPE®

FEXLCSC42

Ordering Tree



Mechanical Specifications

Cable Retention Strength, maximum $11.24 \text{ lb} @ 0 \degree + 4.40 \text{ lb} @ 90 \degree$

Optical Specifications

Fiber Mode Multimode

Fiber Type OM4, LazrSPEED®

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \text{ (+14 }^{\circ}\text{F to } +140 \,^{\circ}\text{F)}$

Environmental Space Riser

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



Included Products

460125198 – Pre-Radiused LC Connector duplex for 1.6 mm Fiber, multimode

460125750 – LazrSPEED® Pre-Radiused SC Connector for 1.6 mm Fiber Cordage, Duplex,

multimode

760103028

Page 2 of 3



FEXLCSC42

R-002-ZC-5K-F16BL

LazrSPEED® 1.6 mm Riser Zipcord Cable

