



### Main

|                       |  |
|-----------------------|--|
| Product               | General Purpose Current Transformer    |
| Certifications        | UL Recognized                          |
| Ratio                 | 75/5                                   |
| Enclosure Type        | NEMA 1                                 |
| Phase                 | 1 phase                                |
| Power Rating          | 1.5 VA                                 |
| Electrical Connection | Flying leads 24 in (609.60 mm), AWG 16 |
| Opening Size          | Ø 1.13 in                              |

### Ordering and shipping details

|                     |                                   |
|---------------------|-----------------------------------|
| Category            | 15500 - CLASS 4210 CT'S (LC 5101) |
| Discount Schedule   | PA1                               |
| GTIN                | 00785901099048                    |
| Package weight(Lbs) | 1 lb(US) (0.45 kg)                |
| Returnability       | No                                |
| Country of origin   | MX                                |

### Offer Sustainability

|                             |   |
|-----------------------------|---|
| California proposition 65   | WARNING: This product can expose you to chemicals including: Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation            | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC          | Yes   |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free      | Yes   |
| Mercury free                | Yes   |
| RoHS exemption information  | <a href="#">Yes</a>   |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>  |
| PVC free                    | Yes   |
| Halogen content performance | Halogen free plastic parts product  |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.