


XVS96BMBN

Electronic alarm, Harmony XVS, black, NPN, mounting support DIN 96, 0...96dB, 16tones, 4 channels, 12...24V AC DC



Main

Range of Product	Harmony XVS
Product or Component Type	Electronic alarm
Device short name	XVS

Complementary

Color	Black
Material	PC (polycarbonate): terminal cover PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene): body
Marking	CE
Overvoltage category	Class II IEC 61140
Mounting Support	96 mm DIN rail
[Us] rated supply voltage	12...24 V DC
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	250 mA 12 V 292 mA 12 V 292 mA 24 V 354 mA 24 V
Clamping Connection Capacity	$\leq 1 \times 1.5 \text{ mm}^2$
Width	3.78 in (96 mm)
Height	3.78 in (96 mm)
Depth	2.29 in (58.1 mm)
Net Weight	0.88 lb(US) (0.4 kg)

Environment

Discrete output type	NPN
Signalling type	16 tones alarm
Standards	IEC 60947-5-1 IEC 60947-1
Protective treatment	TC
Ambient Air Temperature for Storage	-31...158 °F (-35...70 °C)
Ambient Air Temperature for Operation	-4...122 °F (-20...50 °C)
IP degree of protection	Panel mounted IP54 IEC 60529
Noise level	0...96 dB continuous or intermittent tone)1 m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	22617-XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	3606480072017
Returnability	No
Country of origin	JP

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.31 in (13.5 cm)
Package 1 Width	5.55 in (14.1 cm)
Package 1 Length	5.55 in (14.1 cm)
Package 1 Weight	18.66 oz (529.0 g)
Unit Type of Package 2	S04
Number of Units in Package 2	16
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	21.07 lb(US) (9.556 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	320
Package 3 Height	47.24 in (120.0 cm)
Package 3 Width	31.50 in (80.0 cm)
Package 3 Length	125.98 in (320.0 cm)
Package 3 Weight	373.20 lb(US) (169.28 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Electronic Alarm

Dimensions

