NSYMR1210

Monobloc perforated plates H1200xW1000mm with universal perforations 11x26mm





Main	
Range	Spacial
Accessory / separate part category	Mounting accessory
Product or Component Type	Mounting plate
Device Application	Multi-purpose
Enclosure nominal dimensions	- H: 47.24 in (1200 mm) W: 39.37 in (1000 mm)
Mounting Location	Direct fixing on backstuds Step slide
Mounting plate description	Telequick perforated
Range compatibility	Spacial Spacial S3D Spacial Spacial CRN Spacial Spacial S3X Thalassa Thalassa PLM
Quantity per Set	Set of 1

steel

Zinc coated

Complementary

Fixing mode	Screwed on backstuds M8 By fixing element		
Permanent permissible load	600.10 Lb(US) (272.2 kg) S3D, CRN, S3X enclosures 360.02 lb(US) (163.3 kg) PLM enclosure		
Maximum load	551.16 Lb(US) (250 kg) S3D, CRN, S3X enclosures 330.69 lb(US) (150 kg) PLM enclosure		
Height	45.08 in (1145 mm)		
Width	37.44 in (951 mm)		
Surface and useful surface	11.72 ft² (108.9 dm²)		
Thickness	0.08 in (2 mm)		
Net Weight	17.20 lb(US) (7.8 kg)		
Number of slots	2325	2325	
Variant particularity	Installation in rear of enclosure	Installation in rear of enclosure	
Cut-out dimensions	11 x 26 mm	11 x 26 mm	

Material

Surface Finish

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES	
Discount Schedule	ES1	
GTIN	3606480183577	
Returnability	No	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	45.28 in (115.0 cm)	
Package 1 Width	37.48 in (95.2 cm)	
Package 1 Length	0.67 in (1.7 cm)	
Package 1 Weight	17.20 lb(US) (7.8 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

	•	
Warranty	18 months	