

KEYWERKS™ MULTIMEDIA MODULES & INSERTS

PDS-0048



DESCRIPTION

Wirewerks offers a wide variety of keystone connector modules designed to create a customized multimedia solution. Keywerks multimedia modules are compatible with all Keywerks keystone faceplates, patch panels and surface mount boxes for transmissions through fiber optic and copper. They are compatible with any standard keystone footprint and can be used in any single or double ganged faceplate, surface mount boxes and patch panels.

FEATURES and BENEFITS

- Quick and easy installation with snap-in mechanism
- Compatible with Keywerks faceplates, patch panels and surface mount box
- Fiber optic and copper multimedia modules
- Available in almond, white and black
- Fits into any standard Keystone style opening

APPLICATIONS

- Telecommunication room and equipment room connections
- Equipment room
- Consolidation point connections
- Multimedia work area outlet

ORDERING
INFORMATION

RJ45 Module Dust Cap (10 per bag)										
KW-DUSTCAP-YY*										
CL	GY	BW	WH	YL	RD	BK	PR	AL	BL	GN
clear	grey	brown	white	yellow	red	black	purple	almond	blue	green
BNC Small Footprint Coupler										
KW-CZZ-BNS-YY*										
BK			WH				AL			
black			white				almond			
BNC 75 Ohms Coupler										
KW-CZZ-BNC-YY*										
BK			WH				AL			
black			white				almond			
F-Type 3 GHz Coupler										
KW-CZZ-FTC-YY*										
BK			WH				AL			
black			white				almond			
RCA to F-Type Connector										
KW-CZZ-RFA-YY*										
BK			WH				AL			
black			white				almond			
HDMI Coupler										
KW-CZZ-HDF-WH										
RCA Coupler										
KW-CZZ-RCX***-AA*										
R	W	B	G	Y	BK	WH	AL			
red	white	black	green	yellow	black	white	almond			

*Replace AA or YY by the desired color code

*** Replace X by the desired Insulation color

Keywerks RCA Jack to 110 Idc Module						
KW-CZZ-RCX***-WH						
R		W		Y		
red		white		yellow		
LC Fiber Optic Keystone						
KW-FXX**-LCZ-YY*						
S1	S2	M1	M3	BK	WH	AL
Single Mode	Single Mode APC	Multimode	Multimode OM3	black	white	almond
SC Fiber Optic Keystone						
KW-FXX**-SCZ-YY*						
S1	S2	M1	M3	BK	WH	AL
Single Mode	Single Mode APC	Multimode	Multimode OM3	black	white	almond
ST Fiber Optic Keystone						
KW-FXX**-STZ-YY*						
S1	M1		BK	WH	AL	
single mode	Multimode		black	white	almond	
Keywerks™ 3.5mm Stereo Socket to Terminal Block Module, White						
KW-35TWH						
Speaker Binding Post (pair black and red)						
KW-CZZ-BPM-YY*						
BK		WH		AL		
black		white		almond		
Keystone Blank Insert (10 per bag)						
KW-ZZZ-BLK-YY*						
BK		WH		AL		
black		white		almond		

*Replace AA or YY by the desired color code
*** Replace X by the desired Insulation color
** Replace XX by the desired mode

PACKAGING

Description
Clear poly bag, 1 unit per bag, or otherwise specified.

PHYSICAL
SPECIFICATIONS

Parameter	Value
Plastic material	UL 94V-0 ABS high-impact thermoplastic

MECHANICAL
SPECIFICATIONS

Parameter	Value
Operating temperature	-40° C (-40° F) ~ 75° C (167° F)
Storage temperature	-40° C (-40° F) ~ 85° C (185° F)

STANDARDS
COMPLIANCE**ANSI/TIA-568-C.2**

Balanced Twisted-Pair Telecommunications Cabling and Components Standards.

ANSI/TIA-568-C.3

Optical Fiber Cabling Components Standard

ANSI/SCTE 02 S

Specification for “F” Port, Female, Indoor

TIA-604 series

Fiber Optic Connector Intermateability Standard

TIA-455 series

Standard Test Procedure for Fiber Optic Components

IEC 60603-7

Connectors for Electronic Equipment.

IEC 60169

Radio Frequency Connector

IEC 60958

Digital Audio Interface

UL 94

Tests for Flammability of Plastic Material for Parts in Devices and Appliances.

RoHS

Directive on Restriction of Hazardous Substances.