

Eaton AH6808WDAC

Catalog Number: AH6808WDAC

Eaton manual motor controller, #14-10 AWG, 20/30A, Wall, 600/250V, Back and side, Maintained contact, NEMA 3R, Enclosure: Copperless aluminum, Two-pole, -20-65°C, Single-phase, Toggle switch



General specifications

Product Name	Catalog Number
Eaton manual motor controller	AH6808WDAC
UPC	Product Length/Depth
040893123950	4 in
Product Height	Product Width
12 in	4 in
Product Weight	Compliances
1.23 lb	NAFTA
Certifications	
cULus Listed	

defaultTaxonomyAttributeLabel

Enclosure

NEMA 3R

Special features

With NEMA 3R enclosure

Type

Manual motor controller

Amperage Rating

20/30A

Voltage rating

600/250V

Number Of Poles

Two-pole

Phase

Single-phase

Enclosure material

Copperless aluminum

Application

Industrial

Device grade

Industrial

Wiring method

Back and side, spring-loaded screw

Contact type

Maintained

NEMA Rating

3R

Switch type

Toggle switch

Mounting method

Wall

Closure type

Maintained

Number of positions

2

Resources

Catalogs

[Arrow Hart Buyers Guide Section E](#)

Specifications and datasheets

[Eaton Specification Sheet - AH6808WDAC](#)

Allowable wire size

#14-10 AWG

Operating temperature

-20 to 65 °C

Material

Aluminum

Termination style

Back and side wire

Throw

Single-throw

Terminals

Copper-alloy, brass screw

Color

Gray



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia