



CL70 LED

LOW PROFILE FLUSH MOUNT



NAME:	
TYPE:	
DATE:	
NOTES:	

SPECIFICATIONS

WIRING:	Installs easily in traditional junction boxes (3" or 4").
HOUSING DETAILS:	The AURA low-profile series housings have a corrosion-resistant diecast aluminum construction.
	It features a matte white acrylic diffuser with a unique press-release mechanism for easy removal and maintenance.
	The unit is completely protected from moisture infiltration, giving it its WET location rating.
OPTICS:	LED technology delivers 1000 lumens ($7"$ version) and 2000 lumens (11" version).
ELECTRICAL:	Energy efficient LED utilizing a 120V 60Hz driver. Certifications: ETL and Energy Star listed to U.S. and Canadian safety standards for DAMP & WET locations. Phase Control: Forward Phase
LENS:	LED technology in combination with a white acrylic frosted lens, provides an even light distribution.

COLOR TEMPERATURE:	3K - 4K
OPERATING TEMPERATURE:	-40°C + 40°C
CRI:	80+
LUMEN OUTPUT:	1000 lumens
DIMMABLE:	Yes
WATTS:	14W
LED LIFE:	50,000 hours
WARRANTY:	5 years
VOLTAGE:	120V
DIAMETER:	7.00" (177.8 mm)
HEIGHT:	1.50" (38.1mm)
INTEGRATED MOTION SENSOR:	No

APPLICATIONS

The Aura low-profile series LED flush mounts provide general illumination suitable for indoor or outdoor residential and commercial applications. Ideal for use in closets, foyers, hallways, bedrooms, offices, utility work areas, stairways, and many other rooms in the house or work place environment.






CL70 LED

LOW PROFILE FLUSH MOUNT

DIMENSIONS



RATINGS









ORDERING GUIDE

AURA CL70 SERIES

 Series
 Color Temperature
 Finish

 CL70-14W
 3K 3000K/80CRI/14W
 WH White

4K 4000K/80CRI/14W

Notes: Configure product using BOLD options: Ex: CL70-14W-3K-WH