



Hart lock complex environment locking devices

Product description


2-pole, 3-wire grounding
15A, 125V/AC
NEMA L5-15



2447



25W47



CR5792

Hart lock plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	125	L5-15	Watertight	0.30-0.65" (7.6-16.5mm)	Y	□ 24W47*	□ 25W47*	•	•
			Watertight	0.30-0.65" (7.6-16.5mm)	BK	□ 24W47BK*	□ 25W47BK*	•	•
			Auto grip corrosion resistant	0.33-0.66" (8.4-16.7mm)	Y	□ 4721NCR	□ 4731NCR	•	•

* Not Fed Spec

Hart lock receptacles




Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	Duplex receptacle catalog no.		
15	125	L5-15	Watertight	Y	□ 65W47 ^{Δ†}	□ 65W47DPLX ^{Δ†}	•	•
			Watertight	BK	□ 65W47BK ^{Δ†}	□ 65W47DPLXBK ^{Δ†}	•	•
			Corrosion resistant	Y	--	□ CR4700	•	•
		5-15/ L5-15	Corrosion resistant combination locking & straight blade	Y	--	□ CR5792	•	•

^Δ cULus Listed, [†] Not CSA certified

Hart lock complex environment locking devices

Product description

2-pole, 3-wire grounding
15A, 250V/AC
NEMA L6-15



Hart lock plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	250	L6-15	Watertight	0.30-0.65" (7.6-16.5mm)	Y	□ 24W49	□ 25W49	•	•
			Watertight	0.30-0.65" (7.6-16.5mm)	BK	□ 24W49BK	□ 25W49BK	•	•

Hart lock receptacles



Rating A	V/AC	NEMA	Description	Single receptacle catalog no.	Duplex receptacle catalog no.		
15	250	L6-15	Watertight	□ 65W49	□ 65W49DPLX	•	
			Watertight	□ 65W49BK	□ 65W49DPLXBK	•	

Dimensional information: D-9

Specification information:

Watertight industrial plugs & connectors: D-36
Severe duty industrial plugs & connectors: D-37
Corrosion resistant auto grip industrial plugs & connectors: D-37

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-30

RoHS compliant - Page Q-30