



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ21 ZCKJ8H7 ZCKJ11H7 ZCKJ11H29 ZCKJ5H7 ZCKJD37H29 ZCKJ6H7 ZCKJ1H7 ZCKJ9 ZCKJ6 ZCKJD39 ZCKJD39H7 ZCKJ7H7 ZCKJ8H29 ZCKJD31 ZCKJ21H29 ZCKJD35 ZCKJD39H29 ZCKJ7 ZCKJ8 ZCKJD35H7 ZCKJ2H7 ZCKJ5H29 ZCKJ9H29 ZCKJ1H29 ZCKJ11 ZCKJ7H29 ZCKJ21H7 ZCKJ2 ZCKJD31H29 ZCKJ5 ZCKJ2H29 ZCKJ9H7 ZCKJD31H7 ZCKJ6H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCKJD37
ZCKJ1
ZCKJD37H7
ZCKJD35H29

Movement of operating head	Linear
Type of operator	Side plunger spring return metal
Type of approach	Lateral approach, 1 direction

Complementary

Switch actuation	On end
Positive opening	With
Net weight	0.44 lb(US) (0.2 kg)
Head material	Metal

Environment

Ambient air temperature for operation	50...248 °F (10...120 °C)
Ambient air temperature for storage	50...248 °F (10...120 °C)
Environmental characteristic	High temperature

Packing Units

Package 1 Weight	0.44 lb(US) (0.200 kg)
Package 1 Height	0.041 dm
Package 1 width	0.045 dm
Package 1 Length	0.085 dm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------