

## ORDERING INFORMATION

Order code: 59243  
 Description: F54T5/41K/8/HO/PS/G5/COLDSTART/STD  
 UPC: 69549592438  
 Case quantity: 25




Nominal length : 48 in. (915 mm) Dia. : 1 in. (26 mm)


## PERFORMANCE DATA

Shape:	T8
Base:	G5 (Min Bipin)
Starting method:	Rapid Start (RS)
Wattage (W):	54
Colour temperature (K):	4 100
CRI:	85
Rated life on IS <sup>1</sup> ballast:	
Based on a 3 hour start	24 000
Based on a 12 hour start	30 000
Rated life on PS/PRS <sup>1</sup> ballast:	
Based on a 3 hour start	30 000
Based on a 12 hour start	36 000
Initial lumens (lm):	4 650
Mean lumens (lm):	4 400
Nominal efficiency (lm/W):	86
TCLP compliant:	Yes
Phosphor composition:	Triphosphor
Nominal lamp operating frequency (Hz):	60
<sup>2</sup> Minimum starting temperature (°C):	-10

## DIMENSIONS



## SPECTRAL DISTRIBUTION



<sup>1</sup> The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

<sup>2</sup> The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T8 Cold Start ballast.

