

CH361DS

30A 3P Type4/4X 600VAC/DC Heavy Duty Fusible Safety Switch



Main

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

Complementary

Line Rated Current	30 A
Factory Installed Neutral	None
Mounting Type	Surface
Voltage Rating	600 V AC/DC
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper
Maximum Horse Power Rating	5 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 15 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 7.5 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 20 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 5 Hp 250 V DC 15 hp 600 V DC
Height	14.93 in (379.22 mm)
Maximum Width	8.67 in (220.22 mm) 8.67 in (220.22 mm) 8.67 in (220.22 mm) 8.67 in (220.22 mm)
Depth	5.11 in (129.79 mm)
Tightening torque	45 Lbf.in (5.08 N.m) 0.02 in ² (13.3 mm ²) AWG 6) 4.52 N.M for 8.367 mm ² (AWG 8) 3.95 N.m for 2.06...5.261 mm ² (AWG 14...AWG 10)

Environment

Certifications	CSA
Enclosure Rating	NEMA 4/4X stainless steel 304

Ordering and shipping details

Category	00153 - C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	00785901995166
Nbr. of units in pkg.	1
Package weight(Lbs)	13.78 lb(US) (6.25 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	5.70 in (14.478 cm)
Package 1 width	9.30 in (23.622 cm)
Package 1 Length	17.50 in (44.450 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes