NSYS3DC8625

Wall mounted steel enclosure, Spacial S3DC, plain door, without plain chasis, 800x600x250mm, IP66, IK10





Main

Range	Spacial
Product name	Spacial S3DC
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	31.50 in (800 mm)
Enclosure nominal width	23.62 in (600 mm)
Enclosure nominal depth	9.84 in (250 mm)
Door type	Solid
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 1 lock

Complementary

Body type	Single piece body Gutter-shaped front profile double sheet thickness	
Number of doors	Front face 1	-
Door opening side	Reversible 120 °)	
Lock type	3 points lock, screw driver insert	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	steel	
Surface finish	Epoxy-polyester powder	
Color	Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	UL	
Net Weight	46.30 lb(US) (21 kg)	
Net Weight	46.30 lb(US) (21 kg)	

Environment

NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP66 IEC 60529

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480314148
Returnability	Yes
Country of origin	ES
-	

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.81 in (30.0 cm)
Package 1 Width	25.00 in (63.5 cm)
Package 1 Length	35.04 in (89.0 cm)
Package 1 Weight	46.30 lb(US) (21.0 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	12
Package 2 Height	79.53 in (202.0 cm)
Package 2 Width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	584.23 lb(US) (265.0 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------