



Red Urethane Seal Coat, 311 Grams No. 72044 | Item# 1006118 | Case# 1006117

Product Description Polyurethane coating that insulates electrical equipment and seals out water and moisture. The red formula

provides a striking contrast on the surface where the

product is being used.

Applications On motor windings, terminals, bus bars, commutator

ends, stator coils, and PC boards

Unit Package Description 16 Ounce (473 ml) Aerosol

Brand CRC

Generic Description 1 Urethane Coating

 Net Fill
 311 Grams

 UPC Code
 078254720449

Unit Dimensions 19.69H x 6.68W x 6.68D cm

Units Per Case 12

Case Dimensions 21.86H x 21.33W x 28.7D cm

Cases Per Pallet 133

Case Weight 4.98 kg

1 2 of 5 Code 30078254720440

Appearance Red Liquid

Flash point (F) -4°F

Flash point (C) -20°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.731
Plastic Safe Yes

Evaporation Rate Moderate

Dry Time - Fully Dry 72 Hours

Recoat 72 Hours

Coverage 1.86 to 2.32 Sq M

Dielectric Strength 3,100 Volts/Mil

Working Temp (F) -90 to 250°F

Last revised: 2/13/2019

Page 1 of 2







Working Temp (C) -67.8 to 121.1°C

Propellant Hydrocarbon

Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

Restricted from Sale In: Not for sale in United States.

Removal (How To) Remove: WET paint with mineral spirits or terpentine, DRY

paint with lacquer thinner/stripper.

Last revised: 2/13/2019

Page 2 of 2

