



Main

Product Type	Enclosure
Range of Product	QO

Complementary

Current Rating	125 A
Interrupt Rating	22 kA
Number of Spaces	2
Maximum Number of Single Pole Circuits	2
Maximum Number of Tandem Breakers	0
Number of Phases	1 phase
Enclosure Rating	NEMA 3R outdoor
Breaker Compatibility	Circuit breaker QO 2P
Product Certifications	UL Listed
Wiring Configuration	3-wire
Electrical Connection	Lugs
Wire Size	AWG 12...AWG 2/0 aluminium AWG 14...AWG 2/0 copper
Surface Finish	Baked enamel Gray
Busbar Material	Tin plated copper: busbar
Tightening Torque	35 lb.in, AWG 14...AWG 10, copper 35 lb.in, AWG 12...AWG10, aluminium 40 lb.in, AWG 8...AWG 4, aluminium/copper 50 lb.in, AWG 3...AWG 2, aluminium/copper Main lugs 50 lb.in, AWG 3...AWG 2/0, aluminium/copper
Box Number	13R
Ground Bar	Grounding bar (ordered separately)
Enclosure Material	Welded galvanized steel
Enclosure Type	Enclosure
Height	16.18 in (411 mm)
Width	6.93 in (176 mm)
Depth	4 in (101.60 mm)

Ordering and shipping details

Category	00005-QO,Q2L 2P ENCL & BREAKERS
Discount Schedule	DE2A
GTIN	785901051800
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.00 in (12.7 cm)
Package 1 Width	8.11 in (20.6 cm)
Package 1 Length	17.91 in (45.5 cm)
Package 1 Weight	9.59 lb(US) (4.35 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------