



Main

Range	PowerLogic
Product or Component Type	PT module

Complementary

Associated fuse rating	High voltage F1 - 315 mA High voltage F2 - 315 mA High voltage F3 - 315 mA Voltage F4 - 250 mA Voltage F5 - 250 mA Voltage F6 - 250 mA Voltage F7 - 250 mA
Input voltage	347 V +/- 10 % 600 V +/- 10 %
Output voltage	120 V +/- 0.3 %
Type of Installation	Enclosed outdoor Indoor
Height	8.39 in (213 mm)
Width	13.54 in (344 mm)
Depth	2.13 in (54 mm)
Net Weight	12.50 lb(US) (5.67 kg)

Environment

Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C)
Relative humidity	5...90 % non-condensing
Operating altitude	9842.52 ft (3000 m)
Pollution degree	2

Ordering and shipping details

Category	09796-POWERLOGIC EM40/48 HARDWARE
Discount Schedule	PL1
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.50 lb(US) (1.588 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.