

Project: _____ Type: _____

Drawn by: _____ Catalogue #: _____ Date: _____

*Individual Spec Sheet***LED REFLECTOR****MR16-GU5.3****ORDERING INFORMATION**

Order code: 68264
Model number: MR16/S2/7.5W/30K/25/STD
UPC: 69549015722
Case quantity: 60

PHYSICAL DATA

Dimensions: 1 ¹⁵/₁₆" x 2" (48.5 x 50 mm)
Shape: MR16
Base: GU5.3
Heat sink color: White


PERFORMANCE DATA

Watts (W): 7.5
Volts (V AC & DC) 12
Colour temperature (K)¹: 3 000
Lumen output (lm)²: 570
Lumen per Watts (lm/W): 76
CRI: 90
Life L70 (h)³: 54 000
Beam angle (°): 25
CBCP: 3 268
Power factor: 0.9
Frequency (Hz): 60
Operating temp. range: - 20 °C / - 4 °F to 40 °C / 104 °F

¹ Typical colour temperature range: +/- 5 %² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %³ Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations**3**
yrs
warranty
dimmable**6**
damp
location**RoHS****cUL** us**FC**

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.
Data is based upon tests performed in a controlled environment.
Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

DIMENSIONS



CAUTIONS

- Not compatible with E-Lume recessed trims
- Turn power off before inspection, installation, or removal.
- Suitable for use in totally enclosed luminaires.
- Suitable for use in damp locations.
- Do not open – no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- For complete dimmer and warranty information visit www.standardpro.com.
- Operating temperature: -20°C / -4°F to 40 °C / 104 °F.
- 3 Years Limited Warranty.

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____

Company: _____

Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.
All products are subject to change or may be discontinued any time without notice.