



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCKD XCKP XCMD XCKT
Associated body	ZCMD81L5 ZCP35 ZCMD29L5 ZCP28 ZCT28N12 ZCD25 ZCD31 ZCMD81L1 ZCMD39L1 ZCD26 ZCT21N12 ZCMD21L5 ZCP27 ZCMD21L08U78 ZCD21 ZCT27G11 ZCT28G11 ZCMD21C12 ZCP37 ZCMD41L2 ZCP21 ZCMD25L2 ZCT27N12 ZCT25N12 ZCMD41L1 ZCP25

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCT27P16
 ZCD29M12
 ZCMD39L5
 ZCMD29C12
 ZCMD21L2
 ZCT21G11
 ZCD29
 ZCP21M12
 ZCMD61M12
 ZCMD39L2
 ZCT26N12
 ZCP39
 ZCMD25L1
 ZCT25P16
 ZCD21M12
 ZCT28P16
 ZCD35
 ZCP31
 ZCP29
 ZCD27
 ZCMD81L2
 ZCMD29L2
 ZCT25G11
 ZCMD61C12
 ZCD37
 ZCD28
 ZCMD37L5
 ZCMD29L1
 ZCMD41L5
 ZCMD69C12
 ZCMD21L08R12
 ZCD39
 ZCT26P16
 ZCMD21M12
 ZCMD21L1
 ZCP29M12
 ZCT26G11
 ZCMD37L1
 ZCT21P16
 ZCMD25L5
 ZCP26
 ZCMD37L2

Movement of operating head	Linear
Type of operator	Roller lever plunger spring return thermoplastic
Type of approach	Vertical approach, 1 direction

Complementary

Switch actuation	By 30° cam
Positive opening	With

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.05 lb(US) (0.024 kg)
Package 1 Height	0.200 dm
Package 1 width	0.550 dm
Package 1 Length	0.250 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------