



### Main

Ampere Rating	100mA
Ampere Rating	100mA
Approvals	UL Listed - CSA Certified - CE Marked
Approvals	UL Listed - CSA Certified - CE Marked
Body Type	Tubular
Body Type	Tubular
Connection Type	Cable (2m)
Connection Type	Cable (2m)
Enclosure Material	Nickel Plated Brass
Enclosure Material	Nickel Plated Brass
Enclosure Rating	NEMA 3/4X/6P/12/13
Enclosure Rating	NEMA 3/4X/6P/12/13
Enclosure Type	Water tight, Dust tight, Oil tight, Corrosion Resistant and Submersible (Indoor/Outdoor)
Enclosure Type	Water tight, Dust tight, Oil tight, Corrosion Resistant and Submersible (Indoor/Outdoor)
LED Indicator	Output: Yellow
LED Indicator	Output: Yellow
Marketing Trade Name	Osiprox
Marketing Trade Name	Osiprox
Maximum Operating Frequency	25Hz (AC) - 4000Hz (DC)
Maximum Operating Frequency	25Hz (AC) - 4000Hz (DC)
Maximum Voltage Rating	264V
Maximum Voltage Rating	264V
Nominal Sensing Distance	4mm
Nominal Sensing Distance	4mm
Operating Temperature Range	-13 to 158 Degrees F (-25 to 70 Degrees C)
Operating Temperature Range	-13 to 158 Degrees F (-25 to 70 Degrees C)
Output	AC/DC 2-Wire (Universal) - 1 N.O.
Output	AC/DC 2-Wire (Universal) - 1 N.O.
Sensor Diameter	12mm
Sensor Diameter	12mm
Supply Voltage	24/240VAC - 24/210VDC
Supply Voltage	24/240VAC - 24/210VDC
Type	XS6
Type	XS6

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.