



## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJD39H7 ZCKJD37H29 ZCKJ8 ZCKJ5 ZCKJ6H29 ZCKJ7 ZCKJ5H7 ZCKJ1H29 ZCKJ2 ZCKJ8H29 ZCKJ21H29 ZCKJ5H29 ZCKJ7H29 ZCKJ6H7 ZCKJD31H29 ZCKJD39 ZCKJ2H7 ZCKJ1 ZCKJD31 ZCKJ11 ZCKJ2H29 ZCKJ21H7 ZCKJ9H29 ZCKJD35H7 ZCKJD37H7 ZCKJ11H7 ZCKJ7H7 ZCKJD35 ZCKJ8H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ21  
ZCKJ9  
ZCKJ9H7  
ZCKJ6  
ZCKJ1H7  
ZCKJD37  
ZCKJD35H29  
ZCKJD31H7  
ZCKJD39H29  
ZCKJ11H29

Movement of operating head	Linear
Type of operator	Side plunger spring return metal
Type of approach	Lateral approach, 1 direction

### Complementary

Switch actuation	On end
Positive opening	With
Net weight	0.44 lb(US) (0.2 kg)
Head material	Metal

### Environment

Ambient air temperature for operation	-40...158 °F (-40...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Low temperature

### Packing Units

Package 1 Weight	0.44 lb(US) (0.200 kg)
Package 1 Height	0.300 dm
Package 1 width	0.640 dm
Package 1 Length	1.080 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------