

Kellems Wire Management,
Liquidtight System, Straight, 1/2",
Non-Insulated with Mesh

By Hubbell Wiring Device-Kellems
Catalog # [074093402](#)

Kellems Wire Management, Liquidtight System, Straight, 1/2",
Non-Insulated with Mesh

Features

- Helps prevent conduit pull-out and damage at fitting
- Reduces equipment downtime

Performance

- Environmental - Flammability - UL 94-HB and UL 94-V2
- Environmental - Hazardous Location - Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2
- Environmental - Operating Temperature - -30°F to +225°F (-34°C to +107°C)

General

Catalog Number	074093402
Material	Steel Fitting, Stainless Steel Mesh
Series	Liquidtight Conduit
Style	For Metal & Non-Metallic PolyTuff I
UPC	783585331614

Dimensions

Conduit Trade Size	1/2 in
--------------------	--------

Certifications And Compliance

Industry Standard(s)

UL Listed

Logistics

Carton Quantity	10
Pallet Quantity	3240

Product Assets

- [Catalog Page - WDK W-58 Catalog Page](#)
- [Catalog Page - WDK G-29 Catalog Page](#)
- [Catalog Page - WDK W-67 Catalog Page](#)
- [Catalog Page - WDK W-57 Catalog Page](#)
- [Catalog Page - WDK W-66 Catalog Page](#)
- [Catalog Page - WDK G-42 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Engineering Drawing - 074093402 AutoCAD Drawing](#)
- [Literature - Wire Management Solutions Brochure](#)
- [Literature - Wiring Device Solutions for Strategic Manufacturing Facilities](#)
- [Sales Drawings - WDK_0740934_DRAWINGS_PDF](#)
- [Specifications - Wiring 074093402 Specification Sheet](#)
- [Specifications - 074093402 Specification Sheet](#)
- [Specifications - 74093402 Specification Sheet French](#)
- [Warranty - Industrial & Commercial Products](#)
- [Video - Kellems Wire Management Solutions](#)
- [Video - Kellems Wire Management Solutions](#)

