# La legrand<sup>®</sup>

## WIREMOLD® OFR Series Overfloor Raceway



OFR Series Raceway provides access to power, A/V, and communication services to open-space areas in an ADA compliant low profile design.

# Multiple Services in a Low Profile Overfloor Raceway

OFR Series Overfloor Raceway System provides four-channels of capacity and access to a wide range of power, communications, and A/V connectivity options in the smallest, lowest, narrowest, ADA compliant profile available in overfloor raceway systems. This system installs over existing floor coverings and is both tamperresistant and installer-friendly, making it an ideal solution for relocatable or permanent installations where access through floors and ceilings is not an option. There are also transition fittings to feed OFR Series Raceway from Wiremold wall-mounted raceway systems and Vista Architectural Columns. OFR Series Raceway accepts Wiremold Open System device plates that provide connectivity to a wide range of devices from leading communication and A/V providers.

#### Features & Benefits

- Lowest profile overfloor raceway available. Smaller, narrower, lower raceway profile reduces potential trip hazards while also being installer friendly to speed installations.
- Installs in open space areas. Provides power, communication, and A/V wiring to areas where in-floor or ceiling distribution are not accessible options.
- Multiple channel base. Four-channel raceway provides space for multiple combinations of power, communication and A/V to be provided through a single raceway installation.
- **Black powder coat finish.** Durable textured finish resists scuffing and scratches and blends with most decors.
- Multiple options for communication and A/V connectivity. OFR Series Raceway accepts Wiremold Open System device plates that provide connectivity to a wide range of devices from leading communication and A/V providers.
- Re-energize abandoned poke-thru holes. Brings a wide variety of services to the work surface by re-using existing openings from previous poke-thru installations.

- Attaches directly to floor covering. Works with carpet, tile, wood, etc. so there is no need to remove or alter existing floor coverings. Ideal for both temporary and permanent installations.
- Multiple transition options. Transition fittings are available to feed OFR Series Raceway from Wiremold DS4000<sup>™</sup>, 4000<sup>®</sup>, and 2400 Series<sup>™</sup> wall-mounted raceway systems and also from Vista Architectural Columns.
- **Tamper-resistant system.** Raceway cover is difficult to remove without the proper tools, discouraging unwanted access to raceway-provided services.
- Meets ADA Accessibility Guidelines. Low profile, unobtrusive design meets the ADA Accessibility Guidelines that pertain to ADA Standard 4.5 which addresses changes in floor and ground surface levels.

#### **Vertical Markets**

- Healthcare
- Hospitality
- Entertainment

- Commercial
- Education
- Retail

#### Compliance

cETLus Listed.



#### **OFR Series Overfloor Raceway System Layout**



OFR Series Overfloor Raceway Wire Fill Capacities for Power*												
WIRE SIZE THHN/THWN	O.D. Inches (mm)		WIRE CROSS-SECTIONAL AREA	# OF WIRES PER OUTER CHANNEL (40% FILL)	# OF WIRES PER OUTER CHANNEL w/OFR1 (40% FILL)	# OF WIRES PER OUTER CHANNEL w/OFR9 (40% FILL)	# OF WIRES PER INNER CHANNEL (40% FILL)					
14 AWG	0.111	(2.8)	0.010	18	13	10	19					
12 AWG	0.130	(3.3)	0.013	13	10	7	14					
10 AWG	0.164	(4.2)	0.021	8	6	5	9					
8 AWG	0.216	(5.5)	0.037	4	3	2	5					

\* For additional information refer to Technical Section of Wiremold Product Guide.

OFR Series Overfloor Raceway Wire Fill Capacities for Communications													
	CABLE/WIRE SIZE	O.D. (APPROX DIA.) INCHES (MM)		WIRE CROSS- SECTIONAL AREA	# OF CABLES PER OUTER CHANNEL (40% FILL)	# OF CABLES PER OUTER CHANNEL W/OFR1 (40% FILL)	# OF CABLES PER OUTER CHANNEL W/OFR9 (40% FILL)	# OF CABLES PER INNER CHANNEL (40% FILL)					
UNSHIELDED	4-Pair, 24 AWG, Cat 3	0.190	(4.8)	0.028	6	4	3	6					
TWISTED PAIR	4-Pair, 24 AWG, Cat 5e	0.210	(5.3)	0.035	5	3	2	5					
	4-Pair, 24 AWG, Cat 6	0.250	(6.4)	0.049	3	2	2	3					
	4-Pair, 24 AWG, Cat 6a	0.354	(9.0)	0.098	1	1	1	2					
COAXIAL	RG6/U	0.270	(6.9)	0.057	3	2	1	3					
FIBER	ZipCord	0.118 x 0.236	(3 x 6)	0.025	7	5	3	7					
	Round 4-Strand Fiber	0.187	(4.7)	0.027	6	4	3	6					
	Round 6-Strand Fiber	0.256	(6.5)	0.051	3	2	1	3					



Four-channel base of OFR Series Overfloor Raceway provides channels for multiple combinations of services.



OFR Series Raceway features the lowest profile available in overfloor raceway systems.



Tamper-resistant feature prevents unwanted access to raceway-provided services.

### **OFR Series Overfloor Raceway Ordering Information**



**Country of Origin: Mexico** 



## **OFR Series Overfloor Raceway Ordering Information**



3 15/16" (100mm)

## **OFR Series Overfloor Raceway Ordering Information**





5 1/2 (140mm)

#### **OFR Series Overfloor Raceway Ordering Information**



communication modules. **Country of Origin: Mexico** 

inserts and Wiremold Open System





NOTE: All brand and product names referenced in this document are registered trademarks or trademarks of their respective holders.

**NOTE:** The paper used to print this document is an environmentally responsible paper with 10% post consumer waste, with FSC and SFI Chain of Custody certifications, Lacey Act complaint. 100% of the electricity used to manufacture Flo sheets is generated with Green-e certified renewable energy.



Legrand, North America 60 Woodlawn Street West Hartford, CT 06110 1.877.BY.LEGRAND (295.3472)

www.legrand.us Canada 905.738.9195 www.legrand.ca

