

Eaton CRL630C

Catalog Number: CRL630C

Eaton corrosion resistant locking connector , #14-10 AWG, 30A, Industrial, 250V, Back wiring, Yellow, Safety grip, Corrosion resistant, L6-30, Two-pole, Three-wire, Santoprene thermoplastic elastomeric, 0.38 to 1 in



General specifications

Product Name	Catalog Number
Eaton Arrow Hart corrosion resistant locking connector	CRL630C
	UPC
	040893679556
Product Length/Depth	Product Height
2.31 in	4.29 in
Product Width	Product Weight
2.36 in	0.415 lb
Compliances	Certifications
RoHS Compliant	NOM
Federal Specifications Classification W-C375	UL Listed
	CSA certified
	cULus Listed

Electrical Ratings

Amperage Rating

30A

NEMA configuration

L6-30

Operating temperature

-20 to 75 °C (-4 to 167 °F)

Voltage rating

250 V

Wiring method

Back

Product Specifications

Allowable wire size

#14-8 AWG

Application

Industrial

Cord diameter

0.38-1 in (9.5 mm-25.4 mm)

Design type

Industrial grip

Device grade

Extra heavy-duty industrial specification grade

Number Of Poles

Two-pole

Type

Locking connector

Environmental Specifications

Environmental conditions

Corrosion resistant

Environmental resistance

Corrosion resistant

Material Specifications

Color

Yellow

Contact material

Nickel plated brass

Face/body material

Nylon

Material

Nylon

Resources

Brochures

[Complex environment devices brochure](#)

Specifications and datasheets

[Eaton Specification Sheet - CRL630C](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)