

## BSH0553P02F2A

servo motor BSH, Lexium 05, 1.3N.m,  
3000rpm, 55mm, untapped shaft, Sincos multi  
turn, with brake, 3 phases, IP50





## Main

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product or Component Type | Servo motor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Device short name         | BSH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Maximum mechanical speed  | 9000 rpm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Continuous stall torque   | 9.29 Lbf.In (1.05 N.m) LXM32.U60N4 1.5 A, 480 V, three phase<br>9.29 Lbf.In (1.05 N.m) LXM32.U60N4 1.5 A, 400 V, three phase<br>11.51 Lbf.In (1.3 N.m) LXM05AD10M2, 200...240 V, single phase<br>11.51 Lbf.In (1.3 N.m) LXM05BD10M2, 200...240 V, single phase<br>11.51 Lbf.In (1.3 N.m) LXM05CD10M2, 200...240 V, single phase<br>11.51 Lbf.In (1.3 N.m) LXM05AD10M3X, 200...240 V, three phase<br>11.51 Lbf.In (1.3 N.m) LXM05BD10M3X, 200...240 V, three phase<br>11.51 Lbf.In (1.3 N.m) LXM05CD10M3X, 200...240 V, three phase<br>11.51 Lbf.In (1.3 N.m) LXM15LD13M3, 230 V, single phase<br>11.51 Lbf.In (1.3 N.m) LXM15LD13M3, 230 V, three phase<br>11.51 Lbf.In (1.3 N.m) LXM15LD10N4, 400 V, three phase<br>11.51 Lbf.In (1.3 N.m) LXM05AD14N4, 380...480 V, three phase<br>11.51 Lbf.In (1.3 N.m) LXM05BD14N4, 380...480 V, three phase<br>11.51 lbf.in (1.3 N.m) LXM05CD14N4, 380...480 V, three phase           |
| Peak stall torque         | 30.98 Lbf.In (3.5 N.m) LXM32.U60N4 1.5 A, 480 V, three phase<br>30.98 Lbf.In (3.5 N.m) LXM32.U60N4 1.5 A, 400 V, three phase<br>23.90 Lbf.In (2.7 N.m) LXM15LD13M3, 230 V, single phase<br>28.15 Lbf.In (3.18 N.m) LXM05AD10M2, 200...240 V, single phase<br>28.15 Lbf.In (3.18 N.m) LXM05BD10M2, 200...240 V, single phase<br>28.15 Lbf.In (3.18 N.m) LXM05CD10M2, 200...240 V, single phase<br>23.90 Lbf.In (2.7 N.m) LXM15LD13M3, 230 V, three phase<br>34.25 Lbf.In (3.87 N.m) LXM15LD10N4, 400 V, three phase<br>28.15 Lbf.In (3.18 N.m) LXM05AD10M3X, 200...240 V, three phase<br>34.25 Lbf.In (3.87 N.m) LXM05AD14N4, 380...480 V, three phase<br>28.15 Lbf.In (3.18 N.m) LXM05BD10M3X, 200...240 V, three phase<br>34.25 Lbf.In (3.87 N.m) LXM05BD14N4, 380...480 V, three phase<br>28.15 Lbf.In (3.18 N.m) LXM05CD10M3X, 200...240 V, three phase<br>34.25 lbf.in (3.87 N.m) LXM05CD14N4, 380...480 V, three phase |

|                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nominal output power    | 400 W LXM32.U60N4 1.5 A, 400 V, three phase<br>400 W LXM32.U60N4 1.5 A, 480 V, three phase<br>340 W LXM15LD13M3, 230 V, three phase<br>340 W LXM15LD13M3, 230 V, single phase<br>350 W LXM05AD10M2, 200...240 V, single phase<br>350 W LXM05BD10M2, 200...240 V, single phase<br>350 W LXM05CD10M2, 200...240 V, single phase<br>350 W LXM05AD10M3X, 200...240 V, three phase<br>350 W LXM05AD14N4, 380...480 V, three phase<br>350 W LXM05BD10M3X, 200...240 V, three phase<br>350 W LXM05BD14N4, 380...480 V, three phase<br>350 W LXM05CD10M3X, 200...240 V, three phase<br>350 W LXM05CD14N4, 380...480 V, three phase<br>670 W LXM15LD10N4, 400 V, three phase                                                                                                                                                                                                                                     |
| Nominal torque          | 5.75 Lbf.In (0.65 N.m) LXM32.U60N4 1.5 A, 400 V, three phase<br>5.75 Lbf.In (0.65 N.m) LXM32.U60N4 1.5 A, 480 V, three phase<br>9.56 Lbf.In (1.08 N.m) LXM15LD13M3, 230 V, single phase<br>9.74 Lbf.In (1.1 N.m) LXM05AD10M2, 200...240 V, single phase<br>9.74 Lbf.In (1.1 N.m) LXM05BD10M2, 200...240 V, single phase<br>9.74 Lbf.In (1.1 N.m) LXM05CD10M2, 200...240 V, single phase<br>7.08 Lbf.In (0.8 N.m) LXM15LD10N4, 400 V, three phase<br>9.56 Lbf.In (1.08 N.m) LXM15LD13M3, 230 V, three phase<br>9.74 Lbf.In (1.1 N.m) LXM05AD10M3X, 200...240 V, three phase<br>9.74 Lbf.In (1.1 N.m) LXM05AD14N4, 380...480 V, three phase<br>9.74 Lbf.In (1.1 N.m) LXM05BD10M3X, 200...240 V, three phase<br>9.74 Lbf.In (1.1 N.m) LXM05BD14N4, 380...480 V, three phase<br>9.74 Lbf.In (1.1 N.m) LXM05CD10M3X, 200...240 V, three phase<br>9.74 lbf.in (1.1 N.m) LXM05CD14N4, 380...480 V, three phase |
| Nominal speed           | 6000 rpm LXM32.U60N4 1.5 A, 400 V, three phase<br>6000 rpm LXM32.U60N4 1.5 A, 480 V, three phase<br>3000 rpm LXM05AD10M2, 200...240 V, single phase<br>3000 rpm LXM05BD10M2, 200...240 V, single phase<br>3000 rpm LXM05CD10M2, 200...240 V, single phase<br>3000 rpm LXM05AD10M3X, 200...240 V, three phase<br>3000 rpm LXM05AD14N4, 380...480 V, three phase<br>3000 rpm LXM05BD10M3X, 200...240 V, three phase<br>3000 rpm LXM05BD14N4, 380...480 V, three phase<br>3000 rpm LXM05CD10M3X, 200...240 V, three phase<br>3000 rpm LXM05CD14N4, 380...480 V, three phase<br>3000 rpm LXM15LD13M3, 230 V, single phase<br>3000 rpm LXM15LD13M3, 230 V, three phase<br>8000 rpm LXM15LD10N4, 400 V, three phase                                                                                                                                                                                           |
| Product compatibility   | LXM05AD10M2 200...240 V single phase<br>LXM05BD10M2 200...240 V single phase<br>LXM05CD10M2 200...240 V single phase<br>LXM15LD13M3 230 V single phase<br>LXM32.U60N4 400 V three phase<br>LXM32.U60N4 480 V three phase<br>LXM05AD10M3X 200...240 V three phase<br>LXM05BD10M3X 200...240 V three phase<br>LXM05CD10M3X 200...240 V three phase<br>LXM15LD13M3 230 V three phase<br>LXM05AD14N4 380...480 V three phase<br>LXM05BD14N4 380...480 V three phase<br>LXM05CD14N4 380...480 V three phase<br>LXM15LD10N4 400 V three phase                                                                                                                                                                                                                                                                                                                                                                 |
| Shaft end               | Untapped                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| IP Degree of Protection | IP50 standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|                           |                                   |
|---------------------------|-----------------------------------|
| Speed feedback resolution | 131072 points/turn x 4096 turns   |
| Holding brake             | With                              |
| Mounting Support          | International standard flange     |
| Electrical Connection     | Rotatable right-angled connectors |

## Complementary

|                                       |                                                                                                                                                                                                                                                           |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range Compatibility                   | Lexium 05<br>Lexium 32<br>Lexium 15                                                                                                                                                                                                                       |
| Supply voltage max                    | 480 V                                                                                                                                                                                                                                                     |
| Phase                                 | Three phase                                                                                                                                                                                                                                               |
| Continuous stall current              | 1.7 A                                                                                                                                                                                                                                                     |
| Maximum continuous power              | 0.97 W                                                                                                                                                                                                                                                    |
| Maximum current Irms                  | 8.7 A LXM15LD13M3<br>8.7 A LXM15LD10N4<br>6.5 A LXM05AD10M2<br>6.5 A LXM05AD10M3X<br>6.5 A LXM05AD14N4<br>6.5 A LXM05BD10M2<br>6.5 A LXM05BD10M3X<br>6.5 A LXM05BD14N4<br>6.5 A LXM05CD10M2<br>6.5 A LXM05CD10M3X<br>6.5 A LXM05CD14N4<br>6 A LXM32.U60N4 |
| Maximum permanent current             | 6.5 A                                                                                                                                                                                                                                                     |
| Switching frequency                   | 8 kHz                                                                                                                                                                                                                                                     |
| Second shaft                          | Without second shaft end                                                                                                                                                                                                                                  |
| Shaft diameter                        | 0.35 in (9 mm)                                                                                                                                                                                                                                            |
| Shaft length                          | 0.79 in (20 mm)                                                                                                                                                                                                                                           |
| Feedback type                         | Multiturn SinCos Hiperface                                                                                                                                                                                                                                |
| Holding torque                        | 7.08 lbf.in (0.8 N.m) holding brake                                                                                                                                                                                                                       |
| Motor flange size                     | 2.17 in (55 mm)                                                                                                                                                                                                                                           |
| Number of motor stacks                | 3                                                                                                                                                                                                                                                         |
| Torque constant                       | 0.7 N.m/A 248 °F (120 °C)                                                                                                                                                                                                                                 |
| Back emf constant                     | 41 V/krpm 248 °F (120 °C)                                                                                                                                                                                                                                 |
| Number of motor poles                 | 6                                                                                                                                                                                                                                                         |
| Rotor inertia                         | 0.1553 kg.cm²                                                                                                                                                                                                                                             |
| Stator resistance                     | 10.4 Ohm 68 °F (20 °C)                                                                                                                                                                                                                                    |
| Stator inductance                     | 25 mH 68 °F (20 °C)                                                                                                                                                                                                                                       |
| Stator electrical time constant       | 2.4 ms 68 °F (20 °C)                                                                                                                                                                                                                                      |
| Maximum radial force Fr               | 190 N 8000 rpm<br>200 N 7000 rpm<br>210 N 6000 rpm<br>230 N 5000 rpm<br>240 N 4000 rpm<br>270 N 3000 rpm<br>310 N 2000 rpm<br>390 N 1000 rpm                                                                                                              |
| Maximum axial force Fa                | 0.2 x Fr                                                                                                                                                                                                                                                  |
| Brake pull-in power                   | 10 W                                                                                                                                                                                                                                                      |
| Type of cooling                       | Natural convection                                                                                                                                                                                                                                        |
| Length                                | 7.99 in (203 mm)                                                                                                                                                                                                                                          |
| Centring collar diameter              | 1.57 in (40 mm)                                                                                                                                                                                                                                           |
| Centring collar depth                 | 0.08 in (2 mm)                                                                                                                                                                                                                                            |
| Number of mounting holes              | 4                                                                                                                                                                                                                                                         |
| Mounting holes diameter               | 0.22 in (5.5 mm)                                                                                                                                                                                                                                          |
| Circle diameter of the mounting holes | 2.48 in (63 mm)                                                                                                                                                                                                                                           |
| Net Weight                            | 4.19 lb(US) (1.9 kg)                                                                                                                                                                                                                                      |

## Ordering and shipping details

|                   |                        |
|-------------------|------------------------|
| Category          | 18282-LEXIUM 32 MOTORS |
| Discount Schedule | PC53                   |
| GTIN              | 3389118159082          |
| Returnability     | No                     |
| Country of origin | DE                     |

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 4.84 in (12.3 cm)     |
| Package 1 Width              | 5.04 in (12.8 cm)     |
| Package 1 Length             | 14.84 in (37.7 cm)    |
| Package 1 Weight             | 3.42 lb(US) (1.55 kg) |


## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                       |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                           |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)                                                                                                                                                                                                                                  |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                                      |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                               |
| Circularity Profile        | No need of specific recycling operations                                                                                                                                                                                                                                                    |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                                                                |
| PVC free                   | Yes                                                                                                                                                                                                                                                                                         |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

### Example with Straight Connectors



| Straight connectors |      | Rotatable angled connectors |      | c (without brake) | c (with brake) |
|---------------------|------|-----------------------------|------|-------------------|----------------|
| b                   | b1   | b                           | b1   |                   |                |
| 39.5                | 25.5 | 39.5                        | 39.5 | 176.5             | 203            |

| Straight connectors |      | Rotatable angled connectors |      | c (without brake) | c (with brake) |
|---------------------|------|-----------------------------|------|-------------------|----------------|
| b                   | b1   | b                           | b1   |                   |                |
| 1.55                | 1.00 | 1.55                        | 1.55 | 6.94              | 7.99           |

---

### 400 V 3-Phase Supply Voltage

---

#### Torque/Speed Curves

Servo motor with LXM32-U60N4 servo drive



X Speed in rpm

Y Torque in Nm

1 Peak torque

2 Continuous torque

---

### 480 V 3-Phase Supply Voltage

---

#### Torque/Speed Curves

Servo motor with LXM32-U60N4 servo drive



X Speed in rpm

Y Torque in Nm

1 Peak torque

2 Continuous torque