


Product Datasheet

Characteristic

XCSTE7513

plastic safety switch XCSTE - 2NC -
slow break - 1 entry tapped 1/2" NPT
-24V



Main

range of product	Preventa Safety detection
product or component type	Safety switch
component name	XCSTE
design	Rectangular
material	Plastic
head type	Key operated turret head
contacts type and composition	2 NC
contact operation	Slow-break, simultaneous
solenoid contacts type and composition	1 NC (slow-break)
cable entry	1 entry tapped 1/2" NPT
electromagnet interlocking	Locking on energisation and unlocking on de-energisation of solenoid
[Us] rated supply voltage	24 V (-20...10 %)
electrical connection	Terminal, 1 x 0.5...2 x 1.5 mm ² with or without cable end
number of poles	2
locking options description	With interlocking, locking by solenoid

Complementary

insulation	Double insulated
positive opening	With NC contact
supply voltage type	AC/DC
supply frequency	50/60 Hz
load factor	1
power consumption in VA	10 VA
mechanical durability	1000000 cycles
positive opening minimum force	15 N
minimum actuation speed	0.03 ft/s (0.01 m/s)
maximum actuation speed	1.64 ft/s (0.5 m/s)
[Ie] rated operational current	0.55 A at 125 V utilisation category DC-13, Q300 conforming to EN/IEC 60947-5-1 0.27 A at 250 V utilisation category DC-13, Q300 conforming to EN/IEC

	60947-5-1 3 A at 120 V utilisation category AC-15, B300 conforming to EN/IEC 60947-5-1 1.5 A at 240 V utilisation category AC-15, B300 conforming to EN/IEC 60947-5-1
[Ithe] conventional enclosed thermal current	6 A
[Ui] rated insulation voltage	300 V conforming to CSA C22.2 No 14 500 V conforming to EN/IEC 60947-1 300 V conforming to UL 508
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-5-1
short-circuit protection	10 A cartridge fuse type gG (gl)
actuator forcible withdrawal rtc	500 N
operating rate	10 cyc/mn for maximum durability
safety level	Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1 Can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to EN/IEC 61508
safety reliability data	B10d = 5000000 (value given for a life time of 20 years limited by mechanical or contact wear)
body material	PA (polyamide)
head material	PA (polyamide)
depth	1.3 in (33 mm)
height	3.7 in (94 mm)
width	4.33 in (110 mm)
product weight	0.79 lb(US) (0.36 kg)

Environment

standards	EN 1088/ISO 14119 EN/IEC 60204-1 EN/IEC 60947-5-1 EN/ISO 12100 UL 508 CSA C22.2 No 14
product certifications	CSA UL
protective treatment	TC
ambient air temperature for operation	-13...140 °F (-25...60 °C)
ambient air temperature for storage	-40...158 °F (-40...70 °C)
vibration resistance	5 gn (f = 10...500 Hz) conforming to IEC 60068-2-6
shock resistance	10 gn 11 ms conforming to IEC 60068-2-27
electrical shock protection class	Class II conforming to EN/IEC 61140
IP degree of protection	IP67 conforming to EN/IEC 60529 and EN/IEC 60947-5-1

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1150 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold