

Main

Actuation	CW and CCW
Actuator	Lever Arm with Roller
Actuator Action	Momentary
Ampere Rating	10A
Approvals	UL Listed File Number E164353 CCN NKCR - CSA Certified File Number LR44087 Class 3211-03 - CE Marked
Body Type	Compact
Connection Type	Conduit Entrance (0.5 Inch NPT)
Contact Configuration	1 N.O./1 N.C.
Contact Form	Form Zb - SPDT-DB (Isolated Contacts)
Contact Material	Silver Alloy
Contact Operation	Snap Action
Contact Rating	NEMA A300/Q300
Enclosure Rating	NEMA 1/2/4/6/6P/12/13; IP66
Head Type	Rotary
Maximum Voltage Rating	240VAC/250VDC
Mounting Type	Surface
Operating Temperature Range	-13 to 158 Degrees F
Operating Torque/Force	21.3 Inch-Ounces (0.15Nm)
Shock Resistance	50G
Terminal Type	Screw Clamp
Type	XCKL
Type of Duty	General Duty
Vibration Resistance	25G
Wire Size	(2) #14AWG

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.