



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCMD XCKD XCKT XCKP
Associated body	ZCT26N12 ZCP37 ZCMD21L08R12 ZCT27G11 ZCMD81L1 ZCMD21L2 ZCT28G11 ZCMD37L2 ZCMD61M12 ZCT27N12 ZCMD81L5 ZCMD37L1 ZCMD41L1 ZCT26G11 ZCP28 ZCP31 ZCP21M12 ZCT21N12 ZCMD29L5 ZCMD41L2 ZCP21 ZCP29 ZCT25P16 ZCD39 ZCMD21L5 ZCD27 ZCD21M12 ZCT28P16

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCMD29L1
 ZCMD37L5
 ZCD28
 ZCT25N12
 ZCD37
 ZCMD25L2
 ZCT26P16
 ZCMD21L1
 ZCD35
 ZCMD61C12
 ZCD29
 ZCMD21L08U78
 ZCD26
 ZCMD29L2
 ZCP27
 ZCMD39L5
 ZCD29M12
 ZCMD25L1
 ZCP29M12
 ZCT28N12
 ZCT27P16
 ZCP26
 ZCP35
 ZCT21P16
 ZCMD39L2
 ZCP25
 ZCD21
 ZCP39
 ZCMD69C12
 ZCMD21M12
 ZCMD25L5
 ZCT25G11
 ZCMD29C12
 ZCD25
 ZCMD41L5
 ZCMD39L1
 ZCMD21C12
 ZCD31
 ZCT21G11
 ZCMD81L2

Movement of operating head	Linear
Type of operator	Ball bearing plunger spring return metal
Type of approach	Multi-directional approach

Complementary

Switch actuation	By 30° cam
Positive opening	With

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.04 lb(US) (0.019 kg)
Package 1 Height	0.150 dm
Package 1 width	0.300 dm
Package 1 Length	0.150 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------